

DICO-C50 BK

50W IP66 2-WAY SLIM COLUMN SPEAKER BLACK

DICO-C50 BK

The HELVIA DICO series column speakers were designed to bring together two key elements: acoustic performance and modern aesthetics.

Each model uses **50×90mm full-range drivers** with a **slim, runway-shaped profile** -equivalent to a standard 2.5" transducer - paired with **1" point-source tweeters**. This setup works like a **mini line array**, minimizing unwanted reflections from floors and ceilings. The result is **crystal-clear voice reproduction** and enhanced overall definition across the full frequency range, from **120Hz up to 20kHz**.

The longer the array, the more extended the **cylindrical sound wave** it generates - keeping sound levels consistent even at greater listening distances compared to conventional point-source systems. When paired with a **subwoofer system**, the DICO speakers deliver **deep, well-balanced lows** for a **smooth and immersive sound experience**.

Equipped with a **line transformer and a 3-position selector**, the DICO columns can easily connect to both **constant-voltage amplifiers (70V/100V)** and **low-impedance systems**. The protections on the connections and connection cables also make them **waterproof** and suitable for indoor and outdoor use, with an **IP66** protection rating.

Aesthetically, the slim and stylish profile blends seamlessly into architectural installations or modern minimalist environments. With lighter weight, compact size, and included wall-mount accessories, DICO column speakers are the perfect choice for conference rooms, worship venues, classrooms, auditoriums, and design-focused installations.

Each column comes with a wall mounting bracket with both horizontal and vertical adjustment.

58f75ee3-9ec4-4a56-a238-2fe736bbb678.png

08377608-aad8-4831-831b-cce100c13457.png

31ebb7cc-3b86-4547-8538-c6c6

IP66

Low Impedance 2-Way Speaker 70V-100V Line

DICO-C50 BK

50W IP66 2-WAY SLIM COLUMN SPEAKER BLACK

PRODUCT DETAILS

KEY FEATURES

- Advanced acoustic design to reduce floor and ceiling reflections.
- Full-range, runway-shaped 50 x 90 mm transducers and 1" tweeter
- Frequency response for excellent speech clarity
- 70V/100V low-impedance line transformer with 3-position selector
- Waterproof enclosure with IP66 protection rating
- Slim, elegant design, ideal for architectural integration
- Suitable for conference rooms, houses of worship, classrooms, auditoriums, and design environments
- Professional bracket with horizontal and vertical adjustment
- Black Color

SPECIFICATIONS

Speaker Type	2-Way Passive
IP Rating	IP66
RMS Power (@ 8ohm)	25W
Program Power (@ 8ohm)	50W
Maximum SPL	105 dB
Freq. Response	120Hz-20KHz
Sensitivity	88dB
Impedance	8?
Woofer	2x 50x90mm Runaway-Shaped Full-frequency
Tweeter	1"

DICO-C50 BK

50W IP66 2-WAY SLIM COLUMN SPEAKER BLACK

Input Voltage	70V - 100V
Power Tap Selector	12.5W/25W/50W (100V) - 6.75W/12.5W/25W (70V) - 50W @ 8ohm
Bracket	Pan/Tilt adjustable bracket (0°/5°/10°/15°) with screws
Dispersion Angle	140°(H)×20°(V)
Finish	Black
Product Size - No Bracket (WxDxH)	75 x 110 x 330 mm (2.95 x 4.33 x 12.99 inch)
Speaker Weight (single unit, no bracket)	1.92 kg – 4.23 lbs.
Packing Size (WxDxH)	460 x 310 x 370 mm (18.11 x 12.20 x 14.57 inch)
Shipping Weight (4 pcs.)	14.5 kg - 31.97 lbs.