

**GLOBE-5140XW****5.25", 40W 2-WAY OPEN-CEILING PENDANT SPEAKER  
(WHITE)**

When elegance and attention to detail are key ingredients in the installation of sound projectors suspended from open ceilings, such as warehouses, buildings with very high ceilings, etc., the new HELVIA Globe X series speakers become crucial elements in the sound reinforcement of environments.

As coaxial speakers with 40W and 60W nominal power outputs, they can be used in a myriad of applications. The 5.25" or 6.5" PP woofers and 1" silk dome tweeters ensure a very wide frequency response that, when paired with any subwoofer, offers audio quality far beyond the standard.

The 5-position line transformer allows for coupling to both constant voltage and low impedance amplifiers.

The speaker comes with all the accessories needed for mounting to open ceilings. An optional kit (GLOBE-51WMW) for wall mounting with adjustable tilt is also available.



GLOBE-5140XW

## 5.25", 40W 2-WAY OPEN-CEILING PENDANT SPEAKER (WHITE)

### PRODUCT DETAILS

#### KEY FEATURES

Stylish design for minimal visual impact

Designed for Open-Ceiling Fixed Installations

High quality materials

5.25" PP Cone Woofer

1" Silk Dome Tweeter

40W Nominal Power @ 8ohm

70V/100V Built-in Line Transformer

5 Power Taps (including 8ohm full power)

#### SPECIFICATIONS

2-Way Pendant Speaker

**Power (Nominal/RMS)** 40W/30W @ 8ohm

**Woofer** 5.25", PP Cone

**Tweeter** 1" Silk Dome

**Frequency Response** 50Hz-20kHz

**Sensitivity (1m@1w)** 88dB

**Transformer tapping @ 70V** 20W - 10W - 5W - 2.5W - 8?

**Transformer tapping @ 100V** 40W - 30W - 20W - 10W - 8?

**Accessories** Hanging kit (included); Wall mount kit (optional - GLOBE-51WMB)

GLOBE-5140XW

**5.25", 40W 2-WAY OPEN-CEILING PENDANT SPEAKER  
(WHITE)****Finish**

White

**Speaker Dimension (ØWxH)**

190 x 250 mm (7.48 x 9.84 in)