


VENU 218v2

REFLEX SUBWOOFER WITH DOUBLE HIGH-EXCURSION 18" TRANSDUCER, 4 ?, 2400 W AES (BLACK)

The Venu 218 V2 is a passive subwoofer featuring dual 18" transducers, engineered to deliver **powerful and accurate low-frequency reproduction** for both fixed and mobile applications. With its **dual reflex-loaded configuration** and **high-excitation drivers with 4" voice coils**, the Venu 218 V2 ensures **deep extension down to 37 Hz**, while maintaining **high efficiency and superior dynamic response**.

The enclosure, built entirely from **18 mm birch plywood**, is solid and reliable, and includes a **recessed connector panel** that allows for flush-to-wall installation.

Designed for environments such as bars, clubs, lounges, hotels, and restaurants, the Venu 218 V2 is the ideal choice for those seeking **extended low-end performance** with **professional-grade output**.



VENU 218v2

REFLEX SUBWOOFER WITH DOUBLE HIGH-EXCURSION 18" TRANSDUCER, 4 ?, 2400 W AES (BLACK)

HIGHLIGHTS

POWER AND PRECISION

The **18" high-excitation driver** with **4" copper voice coil** delivers tight response and excellent thermal durability, ensuring **defined low-end even at high SPL levels**.

DUAL REFLEX SYSTEM DESIGN FOR DEEPER BASS

The compact dual reflex design allows for extended playback down to 37 Hz, making the Venu 218 V2 perfect for environments that require intense bass without excessive bulk.

VENU 218v2

REFLEX SUBWOOFER WITH DOUBLE HIGH-EXCURSION 18" TRANSDUCER, 4 ?, 2400 W AES (BLACK)

PRODUCT DETAILS

KEY FEATURES

Recessed connector panel for discreet flush-wall placement without sacrificing accessibility or robustness

18mm birch plywood cabinet, compact and durable

Bracket positions available for wall or ceiling mounting

M20 top hat fixture included to allow for use in touring applications

Fine textured polyurethane finish, resistant to scratches and impacts, perfect for high traffic public environments

SPECIFICATIONS

Frequency response	37 Hz - 180 Hz ±3 dB
Efficiency	100 dB 1W/1m
Crossover points	80 Hz - 160 Hz active
Nominal impedance	4 ?
Power handling	2400 W AES
Maximum output	132 dB cont, 138 dB peak
Driver configuration	2x 18" LF
Connectors	1x Phoenix with link out and 1x speakON™
Weight	78.87 kg
Dimensions (W x H x D)	1100mm x 557mm x 636mm
Enclosure	18 mm birch plywood
Mounting	Optional M20 top hat fixing point

VENU 218v2

**REFLEX SUBWOOFER WITH DOUBLE HIGH-EXCURSION
18" TRANSDUCER, 4 ?, 2400 W AES (BLACK)**

Finish	Textured polyurethane
Grille	Perforated steel with foam filter
Colors	Black