


RIDER-DELUXE-M v2 AGR

DOUBLE CUTAWAY ELECTRIC GUITAR WITH 2 SINGLE COILS + SPLITTABLE HUMBUCKER AND SELF-LOCKING TUNERS (WILKINSON EQUIPPED)

RIDER DELUXE v2: here it comes the upgraded version of an incredible series gathering the **alder** sonic feature enriched by a **flamed maple top**, the stunning look and feel of **roasted maple**, the original **Wilkinson pick ups/bridge**, the hi-quality **self locking machines heads**.

The upgraded **2-point Wilkinson bridge** provides stability and reliability while Wilkinson single coils in conjunction with the **splittable humbucker** deliver that tone which became a trademark in music history. A fine crafted instrument boasting an undisputed character.



RIDER-DELUXE-M v2 AGR

DOUBLE CUTAWAY ELECTRIC GUITAR WITH 2 SINGLE COILS + SPLITTABLE HUMBUCKER AND SELF-LOCKING TUNERS (WILKINSON EQUIPPED)

HIGHLIGHTS

FLAMED MAPLE TOP & ALDER BODY



All the beauty and the brightness of a flamed maple top over the iconic alder body.

ROASTED MAPLE NECK AND FRETBOARD

Look, touch and feel the roasted maple under your fingers.



RIDER-DELUXE-M v2 AGR

DOUBLE CUTAWAY ELECTRIC GUITAR WITH 2 SINGLE COILS + SPLITTABLE HUMBUCKER AND SELF-LOCKING TUNERS (WILKINSON EQUIPPED)



EQUIPPED BY WILKINSON®

Wilkinson® 2 point bridge and Wilkinson® single coils/splittable humbucker add great value and versatility.

SELF LOCKING TUNERS

Fast restringing and stabler tuning.



RIDER-DELUXE-M v2 AGR

DOUBLE CUTAWAY ELECTRIC GUITAR WITH 2 SINGLE COILS + SPLITTABLE HUMBUCKER AND SELF-LOCKING TUNERS (WILKINSON EQUIPPED)

PRODUCT DETAILS

KEY FEATURES

Body: alder

Top: flamed maple

Neck and Fretboard: satin roasted maple

Frets: 22 (perloid)

Machine heads: hi quality self-locking chrome

Bridge: Wilkinson 2-point tremolo

Pick ups: 2 Wilkinson single coils + 1 Wilkinson splittable humbucker with push/pull

Switch: 5 way

Pots: volume/tone/tone + push/pull

Pickguard: white

Colour: aqua green flamed

Equipped with D'Addario XL

SPECIFICATIONS

Nut	43 mm
Radius	15" (380 mm)
Scale	648 mm
Truss Rod	Bi-directional