

Q-AIR IP IP65 BATTERY POWERED PAR 9X12W

The **Portrait Q Air IP PAR** is meticulously engineered for lighting professionals who demand **flexibility, reliability, and outstanding performance**. Featuring **9x12W 6-in-1 LEDs**, it delivers **exceptional color accuracy** and a rich, full-spectrum output, ideal for creating **vibrant and dynamic atmospheres** in live events, architectural projects, and temporary installations.

Equipped with an **integrated rechargeable battery**, it provides up to **15 hours of continuous operation**, freeing users from the constraints of constant power connections and enhancing mobility on any set or venue.

Its **IP65-rated housing** ensures full protection against water and dust, making it suitable for both **indoor and outdoor applications**, while the **compact and lightweight design** simplifies transport, rigging, and installation without compromising durability.

With **versatile control options**, including DMX compatibility and intuitive on-board settings, the Portrait Q Air IP PAR allows precise **color mixing, dimming, and dynamic effects**, giving lighting designers complete creative freedom.

In summary, the Portrait Q Air IP PAR combines **portability, robust construction, and professional-grade lighting performance**, making it a top-tier solution for **demanding, high-standard lighting applications**.

IP65



Q-AIR IP
IP65 BATTERY POWERED PAR 9X12W



Q-AIR IP IP65 BATTERY POWERED PAR 9X12W

HIGHLIGHTS



PROFESSIONAL-GRADE COLOR PERFORMANCE

Equipped with **9x12W 6-in-1 LEDs**, the Portrait Q Air IP PAR delivers **vibrant, precise, full-spectrum colors**, perfect for creating **dynamic and engaging atmospheres** in live events, architectural projects, and temporary installations. Advanced color mixing ensures smooth tones and complex lighting effects without compromise.

EXCEPTIONAL PORTABILITY AND AUTONOMY

With its **integrated rechargeable battery**, the fixture provides up to **15 hours of continuous operation**, eliminating the need for direct power and making it ideal for **mobile setups or outdoor use**. Its **compact and lightweight design** simplifies transport, mounting, and positioning, even in tight spaces.



Q-AIR IP IP65 BATTERY POWERED PAR 9X12W



RUGGED OUTDOOR VERSATILITY

The **IP65-rated housing** ensures safe operation **indoors and outdoors**, while **advanced control options** – including DMX compatibility and intuitive onboard settings – allow precise management of **dimming, color, and dynamic effects**. It is the ideal solution for professionals who demand **reliability and high performance** in any lighting environment.

Q-AIR IP

IP65 BATTERY POWERED PAR 9X12W

PRODUCT DETAILS

KEY FEATURES

The Portrait Q Air IP PAR features a durable aluminum housing that is compact and lightweight, facilitating transport, mounting, and installation in any venue.

Its IP65-rated design ensures reliable operation indoors and outdoors and provides full protection against water jets and dust from any direction.

The fixture is equipped with 9x12W 6-in-1 LEDs (RGBWA+UV) that allow for dynamic visual effects and fully customizable lighting atmospheres.

It supports a wide DMX addressing range from 001 to 507 and selectable 6, 8, or 12 channel modes for flexible programming in any environment.

The strobe function has variable frequency from ultra-slow to high-speed, enabling rhythmic accents and chase sequences.

Manual RGBWA+UV color control allows precise adjustment for custom lighting scenes and creative designs.

Four selectable PWM refresh rate frequencies ensure flicker-free performance across live events, studios, and broadcast applications.

The fixture comes with 63 static color presets and 24 automatic programs with adjustable speed for rapid setup without complex programming.

The sound-synchronized mode allows lighting effects to follow the music rhythm, making it ideal for concerts, shows, and events.

The integrated rechargeable battery supports up to 15 hours of continuous operation with a 4–6 hour charging time and includes charge-and-operate functionality for uninterrupted performance.

SPECIFICATIONS

Input Voltage	AC 90V–240V 50/60Hz
Power Consumption	108 W
Battery	Integrated rechargeable battery
Battery Runtime	Up to 15 hours

Q-AIR IP IP65 BATTERY POWERED PAR 9X12W

Charging Time	4–6 hours
Light Source	9x12W RGBWAUV LEDs (6-in-1)
Beam Angle	20°
LED Life Span	50,000 hours
Flicker-Free	Yes, adjustable refresh rate from 1200Hz to 6000Hz
Display	Backlit LCD display
Color Rendering Index (CRI)	? 80
Color Range	Nearly unlimited color mixing / Millions of color combinations
Dimmer	0%–100% (0–255)
Ambient Temperature	-10°C – 40°C (14°F – 104°F)
DMX Channels	6, 8, and 12 channel modes
Control Mode	Manual, Auto, RF, Wireless, DMX, Master/Slave, Sound
Positioning / Mounting	Adjustable bracket for flexible positioning / suitable for truss or overhead installation (with use of clamps)
Power Connectors	DC barrel jack
IP Grade	IP65
Cooling	Natural cooling, silent operation
Material	Aluminum
Color	Black
Fixture Dimensions (WxDxH)	133 x 128 x 133 mm (5.23 x 5.03 x 5.23 in.)
Product Weight	2.5 kg (5.51 lbs)