



32330

5 PORT HDMI 4K60 SEAMLESS MULTIVIEW KVM SWITCH

This advanced HDMI® 4K60 switch is capable of displaying up to four sources simultaneously on a single 4K screen, with KVM control via USB Type-B ports. It offers five different multiview modes: Single, PIP, PBP, 3xWIN, and 4xWIN. With the USB roaming function, you can control different sources via KVM simply by moving the mouse pointer from one window to another.

The unit features four HDMI® inputs and one USB Type-C video input. Seamless switching prevents black screens or display interruptions. All functions can be controlled in multiple ways: using the front panel buttons via the OSD menu, the included IR remote control, keyboard hotkeys for KVM selection, the graphical user interface, or via TCP/IP and RS-232 software commands. These versatile features make the switch ideal for a wide range of installations, from professional AV solutions to mission-critical control rooms, including broadcasting, e-sports, and security applications.

It also provides an additional HDMI® output for local monitoring or video capture when paired with an HDMI®-to-USB capture device. The 3.5mm analog and optical TosLink digital audio outputs allow independent audio switching and support multiple audio formats; with LPCM 2.0, volume control is also available.



32330

5 PORT HDMI 4K60 SEAMLESS MULTIVIEW KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

KVM or video management for 4 HDMI® inputs and 1 USB Type-C input

Seamless switching, EDID management, 5 multiview modes, and KVM function with mouse roaming

Control via OSD menu, IR remote control, hotkeys, TCP/IP, and RS-232 commands

3.5mm and TosLink audio outputs with volume control

2-year warranty

SPECIFICATIONS

| | |
|--------------------------------------|---------------------------------------|
| AV Interface | HDMI®, Type-C |
| Console Interface | USB |
| Interface Standards | HDMI® 2.0, USB 2.0 |
| Maximum Supported Resolution | 4096×2160 @60Hz, 4:4:4, 8-bit |
| HDCP Support | 2.2 |
| Audio Support | LPCM, AC3, DD+, DTS, DTS-HD up to 7.1 |
| Separate Audio Ports | 3.5mm, TosLink (Optical) |
| Serial Interface | 4-pin Phoenix |
| Number of Consoles | 1 |
| Maximum Number of PCs/Servers | 5 |
| Cascade Support | No |

32330

5 PORT HDMI 4K60 SEAMLESS MULTIVIEW KVM SWITCH

| | |
|------------------------------|---|
| Switching Methods | OSD menu, IR remote control, hotkeys (KVM), TCP/IP, and RS-232 commands |
| 19" Rack Mountable | No |
| Special Features | Multiview, Seamless switching, USB roaming, volume control |
| Console Interfaces | 2x HDMI® (Female), 2x USB Type-A (Female), 3.5mm Audio (Female), TosLink (Female) |
| PC/Server Interfaces | 4x HDMI® (Female), USB Type-C (Female), 4x USB Type-B (Female) |
| Other Interfaces | RS-232 4-pin Phoenix, RJ45, USB Type-A (Female, service) |
| Power Input | 5.5/2.1 mm |
| Dimensions (W×H×D) | 219 × 146 × 44 mm (8.62 × 5.75 × 1.73 in) |
| Housing Material | Metal |
| Net Weight | 1.3 kg (2.87 lb) |
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -20°C to 60°C (-4°F to 140°F) |
| Humidity | 10–70% RH (non-condensing) |
| Power Supply | 12V DC, 2.5A |
| Color | Black |