

38158

2 PORT 4K HDMI 3D SPLITTER, 2160P30

10.2G HDMI® Splitter for distributing 4K Ultra HD signals from a single source to two screens. It supports resolutions up to 3840x2160 @60Hz, 4:2:0, making it ideal for small to medium installations in shops, bars, or conference rooms. The EDID management feature simplifies installation by optimizing compatibility with different displays and can be connected to any HDMI® source such as media players, satellite receivers, consoles, etc.

Its compact metal design allows easy installation even in tight spaces, for example behind a screen.

HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress, and the HDMI logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



38158

2 PORT 4K HDMI 3D SPLITTER, 2160P30

PRODUCT DETAILS

KEY FEATURES

Sends an HDMI® signal to 2 screens

Supports resolutions up to 4K 60Hz, 4:2:0

EDID management

Compact design

2-year warranty

SPECIFICATIONS

AV Interfaces	HDMI®
Interface Standard	HDMI® 1.4
Supported Bandwidth	10.2 Gbps
Maximum Resolution	3840x2160 @60Hz, 4:2:0, 8-bit
HDCP Support	1.4
Audio Support	Pass-through
Inputs	HDMI® Type-A (Female)
Outputs	2 x HDMI® Type-A (Female)
Power Supply Connector	5.5/2.1 mm
Dimensions (approx. WxDxH)	70 x 60 x 20 mm (2.76 x 2.36 x 0.79 in)
Material	Metal
Net Weight	0.238 kg (0.52 lb)
Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)

38158

2 PORT 4K HDMI 3D SPLITTER, 2160P30

Humidity	20–90% RH (non-condensing)
Power Supply	5V DC, 1A
Color	Black