
38159


4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30


10.2G HDMI® Splitter for distributing 4K Ultra HD signals from a single source to four screens. It supports resolutions up to 3840×2160 @60Hz, 4:2:0, making it ideal for small to medium installations in shops, bars, or conference rooms. The EDID management feature simplifies installation by optimizing compatibility with different displays and can be connected to any HDMI® source such as media players, satellite receivers, consoles, etc. Its compact metal design allows for easy installation even in tight spaces, for example behind a screen.

HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress, and the HDMI logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

38159







Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

38159

4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30

PRODUCT DETAILS

KEY FEATURES

- Sends an HDMI® signal to 4 screens
- Supports resolutions up to 4K 60Hz, 4:2:0
- EDID management
- Compact design
- 2-year warranty

SPECIFICATIONS

AV Interfaces	HDMI®
Interface Standard	HDMI® 1.4
Supported Bandwidth	10.2 Gbps
Maximum Resolution	3840×2160 @60Hz, 4:2:0, 8-bit
HDCP Support	1.4
Audio Support	Pass-through
Inputs	HDMI® Type-A (Female)
Outputs	4 × HDMI® Type-A (Female)
Power Supply Connector	5.5/2.1 mm
Dimensions (approx. W×D×H)	146 × 71 × 25 mm (5.75 × 2.8 × 0.98 in)
Material	Metal
Net Weight	0.407 kg (0.9 lb)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

38159

4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30

Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	20–90% RH (non-condensing)
Power Supply	5V DC, 1A
Color	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it