

38159

# 4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30

10.2G HDMI® Splitter for distributing 4K Ultra HD signals from a single source to four screens. It supports resolutions up to 3840×2160 @60Hz, 4:2:0, making it ideal for small to medium installations in shops, bars, or conference rooms. The EDID management feature simplifies installation by optimizing compatibility with different displays and can be connected to any HDMI® source such as media players, satellite receivers, consoles, etc. Its compact metal design allows for easy installation even in tight spaces, for example behind a screen.

HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress, and the HDMI logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



38159

# 4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30

## PRODUCT DETAILS

### KEY FEATURES

Sends an HDMI® signal to 4 screens

Supports resolutions up to 4K 60Hz, 4:2:0

EDID management

Compact design

2-year warranty

### SPECIFICATIONS

<b>AV Interfaces</b>	HDMI®
<b>Interface Standard</b>	HDMI® 1.4
<b>Supported Bandwidth</b>	10.2 Gbps
<b>Maximum Resolution</b>	3840x2160 @60Hz, 4:2:0, 8-bit
<b>HDCP Support</b>	1.4
<b>Audio Support</b>	Pass-through
<b>Inputs</b>	HDMI® Type-A (Female)
<b>Outputs</b>	4 x HDMI® Type-A (Female)
<b>Power Supply Connector</b>	5.5/2.1 mm
<b>Dimensions (approx. WxDxH)</b>	146 x 71 x 25 mm (5.75 x 2.8 x 0.98 in)
<b>Material</b>	Metal
<b>Net Weight</b>	0.407 kg (0.9 lb)

38159

# 4 PORT 4K HDMI SPLITTER WITH 3D SUPPORT, 2160P30

<b>Operating Temperature</b>	0°C – 40°C (32°F – 104°F)
<b>Storage Temperature</b>	-20°C – 60°C (-4°F – 140°F)
<b>Humidity</b>	20–90% RH (non-condensing)
<b>Power Supply</b>	5V DC, 1A
<b>Color</b>	Black