38152

# 4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS


Matrix for distributing content from multiple sources to multiple displays in any configuration.


This HDMI® 4K60 matrix supports connecting up to 4 HDMI® sources such as PCs, media players, etc., to 4 screens.

It supports resolutions up to 4K@60Hz for high-quality content display—making it an ideal solution for multimedia applications, digital signage, retail environments, and conference rooms.

The matrix can be controlled in multiple ways, via the front panel buttons, IR ports using the included extension cables, and includes a mounting kit for installation in AV rack cabinets.

38152


86bb6743-010a-46de-990a-f07f654faafa.jpg


dbebde2b-ba4c-4888-a85c-0e33348f2b32.jpg

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

38152

# 4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS

## PRODUCT DETAILS

### KEY FEATURES

- Connect up to 4×4K sources to 4×4K screens in any combination
- Supports video resolutions up to 4K@60Hz, 4:4:4, 8-bit
- Control via buttons, IR remote, and Web GUI for flexible management
- EDID management for optimal video performance
- 2-year warranty

### SPECIFICATIONS

| | |
|---|---|
| **AV Interface** | HDMI® |
| **Interface Standard** | HDMI® 2.0 |
| **Supported Bandwidth** | 18 Gbps |
| **Maximum Resolution** | 4096×2160 @60Hz, 4:4:4, 8-bit |
| **HDCP Support** | 2.2 |
| **Audio Support** | Audio Pass-through |
| **IR Support** | 30–60 kHz |
| **Control** | IR, Button |
| **Special Features** | EDID Management |
| **Inputs** | 4 × HDMI® (Female) |
| **Outputs** | 4 × HDMI® (Female) |
| **Control** | RS-232 (Female), 3.5mm (Female) |

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

38152

# 4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS

| | |
|---|---|
| **Power Input** | 5.5/2.1 mm DC socket |
| **Dimensions (W×D×H)** | 220 × 105 × 19 mm (8.66 × 4.13 × 0.75 in) |
| **Material** | Metal |
| **Net Weight** | 0.535 kg (1.18 lb) |
| **Operating Temperature** | 0°C – 40°C (32°F – 104°F) |
| **Storage Temperature** | -20°C – 60°C (-4°F – 140°F) |
| **Humidity** | 20–90% RH (non-condensing) |
| **Power Consumption** | 12V DC, 2.5A |
| **Color** | Black |

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it