

38152

4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS

Matrix for distributing content from multiple sources to multiple displays in any configuration.

This HDMI® 4K60 matrix supports connecting up to 4 HDMI® sources such as PCs, media players, etc., to 4 screens.

It supports resolutions up to 4K@60Hz for high-quality content display—making it an ideal solution for multimedia applications, digital signage, retail environments, and conference rooms.

The matrix can be controlled in multiple ways, via the front panel buttons, IR ports using the included extension cables, and includes a mounting kit for installation in AV rack cabinets.



38152

4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS

PRODUCT DETAILS

KEY FEATURES

Connect up to 4x4K sources to 4x4K screens in any combination

Supports video resolutions up to 4K@60Hz, 4:4:4, 8-bit

Control via buttons, IR remote, and Web GUI for flexible management

EDID management for optimal video performance

2-year warranty

SPECIFICATIONS

AV Interface	HDMI®
Interface Standard	HDMI® 2.0
Supported Bandwidth	18 Gbps
Maximum Resolution	4096x2160 @60Hz, 4:4:4, 8-bit
HDCP Support	2.2
Audio Support	Audio Pass-through
IR Support	30–60 kHz
Control	IR, Button
Special Features	EDID Management
Inputs	4 x HDMI® (Female)
Outputs	4 x HDMI® (Female)
Control	RS-232 (Female), 3.5mm (Female)

38152

4X4 4K UHD HDMI 1.4 MATRIX, 4 INPUTS & 4 OUTPUTS

Power Input	5.5/2.1 mm DC socket
Dimensions (WxDxH)	220 x 105 x 19 mm (8.66 x 4.13 x 0.75 in)
Material	Metal
Net Weight	0.535 kg (1.18 lb)
Operating Temperature	0°C – 40°C (32°F – 104°F)
Storage Temperature	-20°C – 60°C (-4°F – 140°F)
Humidity	20–90% RH (non-condensing)
Power Consumption	12V DC, 2.5A
Color	Black