

38235

## 2 PORT HDMI 18G SPLITTER

The Lindy 2 Port HDMI® 18G Splitter is a compact, high quality solution for distributing HDMI® 2.0 18G signals across dual displays from one source device. With support for resolutions up to 4K 60Hz 4:4:4 8bit, this splitter is great for creating eye-catching digital signage in retail scenarios, showing high quality video in different rooms in medical facilities or ensuring audiences do not miss any of the action in dual display sports bars.

The additional ability to cascade this splitter up to three further levels allows for an extended HDMI® splitting experience, ideal for multi-screen situations such as informational broadcasting in airports, train stations or stock exchange offices. Additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, superior contrasts and a much wider colour gamut, for more lifelike colour. HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players, while a smart EDID management switch on the unit provides maximum compatibility with the display. The splitters durable, compact design also ensures the unit can be installed discreetly, ensuring there is no distraction from the content on screen.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



38235

# 2 PORT HDMI 18G SPLITTER

## PRODUCT DETAILS

### KEY FEATURES

Split a single HDMI® 2.0 source across 2 HDMI® displays

Supports resolutions up to 4K@60Hz 4:4:4, with additional support for HDR

HDCP 2.2 support for enhanced compatibility

EDID Management for hassle free installation

2 Year Warranty

### SPECIFICATIONS

<b>AV Interface</b>	HDMI®
<b>Interface Standard</b>	HDMI® 2.0
<b>Supports Bandwidth</b>	18Gbps
<b>Maximum Resolution</b>	3840x2160@60Hz 4:4:4 8bit
<b>HDCP Support</b>	2.2
<b>Supported Audio</b>	Audio Pass-through
<b>Special Features</b>	EDID emulation
<b>Input</b>	1 x HDMI® (Female)
<b>Output</b>	2 x HDMI® (Female)
<b>Power</b>	5.5/2.1mm DC socket
<b>Dimensions (approx.) WxDxH</b>	100x56x16mm (3.94x2.2x0.63in)
<b>Housing Material</b>	Metal
<b>Net Weight</b>	0.263kg (0.58lb)
<b>Operating Temperature</b>	0°C - 40°C (32°F - 104°F)

38235

## 2 PORT HDMI 18G SPLITTER

<b>Storage Temperature</b>	-20°C - 60°C (-4°F - 140°F)
<b>Humidity</b>	20 - 90% RH (Non-condensing)
<b>Power Requirements</b>	5VDC 1A
<b>Colour</b>	Black