

38236

4 PORT 18G HDMI 2.0 SPLITTER

38236

The Lindy 4 Port HDMI® 18G Splitter is a compact, high quality solution for distributing HDMI® 2.0 18G signals across multiple displays from one source device. With support for resolutions up to 4K 60Hz 4:4:4 8bit, this splitter is great for creating eye-catching digital signage in retail scenarios, showing high quality video in different rooms in medical facilities or ensuring audiences do not miss any of the action in dual display sports bars. Additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, superior contrasts and a much wider colour gamut, for more lifelike colour.

The additional ability to cascade this splitter up to three further levels allows for an extended HDMI® splitting experience, ideal for multi-screen situations such as informational broadcasting in airports, train stations or stock exchange offices.

HDCP 2.2 support ensures there are no issues with a variety of 4K content when connected to source devices including set top boxes, Blu-Ray players and 4K HDR media players, while a smart EDID management switch on the unit provides maximum compatibility with the display. The splitters durable, compact design also ensures the unit can be installed discreetly, ensuring there is no distraction from the content on screen.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

[2153d7d1-2474-49b4-9a66-25689cd9390a.jpg](#)[28edd4c6-0066-476b-8537-7c2dade44d9a.jpg](#)[5f1e6f88-2daf-4fd9-9e9a-f277f46](#)

38236

4 PORT 18G HDMI 2.0 SPLITTER

PRODUCT DETAILS

KEY FEATURES

- Split a single HDMI® 2.0 source across 4 HDMI® displays
- Supports resolutions up to 4K@60Hz 4:4:4, with additional support for HDR
- HDCP 2.2 support for enhanced compatibility
- EDID Management for hassle free installation
- 2 Year Warranty

SPECIFICATIONS

AV Interface	HDMI®
Interface Standard	HDMI® 2.0
Supports Bandwidth	18Gbps
Maximum Resolution	3840x2160@60Hz 4:4:4 8bit
HDCP Support	2.2
Supported Audio	Audio Pass-through
Special Features	EDID emulation
Input	1 x HDMI® (Female)
Output	4 x HDMI® (Female)
Power	5.5/2.1mm DC socket
Dimensions (approx.) WxDxH	163x63x16mm (6.42x2.48x0.63in)
Housing Material	Metal
Net Weight	0.373kg (0.82lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)

38236

4 PORT 18G HDMI 2.0 SPLITTER

Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	20 - 90% RH (Non-condensing)
Power Requirements	5VDC 1A
Colour	Black