

39378

300M CAT.6 VGA, USB & PS/2 KVM EXTENDER COMBO

The Lindy Cat.6 VGA, USB & PS/2 KVM Extender allows users to control a source device such as a PC from a single keyboard, mouse and display up to 300m using a Cat.5e/6 RJ45 cable. Supports analogue resolutions up to 1920x1200 with VGA ports, ideal for managing a PC or workstation from very long distances. The Extender features PC & console ports on the transmitter to connect additional display, keyboard and mouse for local control and console & PC ports on the receiver to connect an additional PC on the remote console side. In both units you can either connect USB or PS/2 keyboard and mouse and PCs using the KVM cables included. It's also possible to connect a second source on the receiver unit and control it pushing the switching button on the front panel or via hotkey. Via OSD menu users can adjust video signal, EDID, enable password protection and change hotkeys.

This extender provides a simple plug & play installation, no additional drivers required, great for both professional and first time users.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.



39378

300M CAT.6 VGA, USB & PS/2 KVM EXTENDER COMBO

PRODUCT DETAILS

KEY FEATURES

Extends VGA, USB and PS/2 up to 300m using a single Cat.6 cable

Supports VGA resolutions up to 1920x1200

Dual console operation - control your computer / KVM Switch from both local and remote locations

Easy, user friendly installation - no software required

2 year warranty

SPECIFICATIONS

AV Interface	VGA
Console Interface	USB, PS/2
Interfaces Standard	VGA, USB (HID), PS/2
Supported Bandwidth	350MHz
Maximum Distance	300m (984.24ft)
Maximum Resolution	1920x1200@60Hz
Transmission Medium	Cat.5e / 6
Special Features	OSD menu, local console switching, remote PC switching
Transmitter KVM Interfaces	Console ports
Transmitter Extension Port	1 x RJ45
Receiver Console Interface	Console ports
Receiver Extension Port	1 x RJ45

39378

300M CAT.6 VGA, USB & PS/2 KVM EXTENDER COMBO

Other Interfaces	USB Type B (Female) for upgrade
Power	5.5/2.5mm DC socket
Dimensions (approx.) WxDxH	130x70x28mm (5.12x2.76x1.1in) (each unit)
Housing Material	Metal
Net Weight	0.3kg (0.66lb) (each unit)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	5VDC 3A
Colour	Black
Unit	Receiver and Transmitter