

39337

4 PORT DVI-I SINGLE LINK, USB 2.0 & AUDIO KVM SWITCH

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

The Lindy 4 Port DVI-I Single Link, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over four DVI equipped PCs from a single keyboard, mouse and monitor.

Supports single link resolutions up to 1920x1200, it can also be used with analogue VGA PCs using adapter cables with support for analogue resolutions up to 2048x1536. The audio output ports on the main unit also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with the 2 ports USB 2.0 hub. Both audio and USB hubs can be switched independently of the computers allowing you to print from one PC whilst working on another for example.

It supports True Transparent USB switching, an advanced USB emulation technology that allows the KVM to recognise specific keyboard & mouse models and emulate any of their associated special key and function information. This also provides enhanced support for combined use with KVM extenders.

The KVM switch features multiple switching options including push buttons on the unit and configurable hotkeys that provide simple, reliable control for the user, great for both professional and first time users.



39337

4 PORT DVI-I SINGLE LINK, USB 2.0 & AUDIO KVM SWITCH



39337

4 PORT DVI-I SINGLE LINK, USB 2.0 & AUDIO KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

Controls four DVI equipped PCs from a single keyboard, mouse and monitor

Switch via the unit's push buttons or keyboard hot keys

Supports DVI-I single link signals, up to 1920x1200

Independent audio switching and 2 ports USB 2.0 Hub for sharing additional USB peripherals

2 year warranty

SPECIFICATIONS

AV Interface	DVI-I
Console Interfaces	USB
Interface Standard	DVI-I Single Link, USB 2.0
Maximum Resolution	DVI
Supported Audio	Analogue Stereo
Separate Audio Ports	2 x 3.5mm (Female)
Console Number	1
Max Number PC/Server	4
Switching Method	Push Buttons & Hotkey Switching
Special Features	USB 2.0 Hub, Independent audio and Hub switching, Active LED Indicators
Console Interfaces	DVI-I (Female), USB 2.0 Type A (Female), 2 x 3.5mm (Female)
PC/Server Interfaces	4 x DVI-I (Female), USB 2.0 Type B (Female), 2 x 3.5mm (Female)

39337

4 PORT DVI-I SINGLE LINK, USB 2.0 & AUDIO KVM SWITCH

Other Interfaces	2 x USB 2.0 Type A (Female) Shared Ports
Power	5.5/2.1mm DC socket
Dimensions WxDxH	255x45x120mm (10.04x1.77x4.72in)
Housing Material	Metal
Net Weight	1kg (2.2lb)
Operating Temperature	0°C - 50°C (32°F - 122°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	0~90% RH (non-condensing)
Power Requirements	9VDC 1.1A
Colour	Silver