42345

2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

42345

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

The Lindy 2 Port HDMI® 18G, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two HDMI equipped PCs from a single keyboard, mouse and monitor set. With integrated cables, this switch can be easily connected directly to the system, with no need to purchase additional cables, saving time and money on installation.

Support for resolutions up to 4096x2160@60Hz 4:4:4 8bit ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including push buttons on the unit alongside hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.

0025094a-b793-4e46-a33f-8e811e71a9fd.jpg a0513933-266c-4b13-add5-7d4287a88bb8.jpg 4c68cd82-b500-4650-8a47-60724

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

42345

2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

- Controls two HDMI® equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push buttons, software or keyboard hot keys
- Supports HDMI® 18G signals, up to 4K 60Hz with 4:4:4 8bit
- Integrated cables for quick, hassle-free installation
- 2 year warranty

SPECIFICATIONS

AV Interface	HDMI®
Console Interfaces	USB
Interface Standard	HDMI® 2.0, USB 2.0
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
HDCP Support	HDCP 2.2
Supported Audio	Analogue Stereo
Separate Audio Ports	2 x 3.5mm (Female)
Console Number	1
Max Number PC/Server	2
Switching Method	Push Button, Hotkey Switching & Software
Special Features	Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators
Console Interfaces	HDMI® Type A (Female), 2 x USB 2.0 Type A (Female), 2 x 3.5mm (Female)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

42345

2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

PC/Server Interfaces	2 x HDMI® (Male), USB 2.0 Type A (Male), 2 x 3.5mm (Male) 1.2m Integrated Cables
Dimensions (approx.) WxDxH	97x25x82.18mm (3.82x0.98x3.24in)
Housing Material	Plastic
Net Weight	0.436kg (0.96lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	Via USB
Colour	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it