

42345


## 2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

The Lindy 2 Port HDMI® 18G, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two HDMI equipped PCs from a single keyboard, mouse and monitor set. With integrated cables, this switch can be easily connected directly to the system, with no need to purchase additional cables, saving time and money on installation.

Support for resolutions up to 4096x2160@60Hz 4:4:4 8bit ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including push buttons on the unit alongside hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.



42345

# 2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

## PRODUCT DETAILS

### KEY FEATURES

Controls two HDMI® equipped PCs from a single keyboard, mouse and monitor

Switch via the unit's push buttons, software or keyboard hot keys

Supports HDMI® 18G signals, up to 4K 60Hz with 4:4:4 8bit

Integrated cables for quick, hassle-free installation

2 year warranty

### SPECIFICATIONS

<b>AV Interface</b>	HDMI®
<b>Console Interfaces</b>	USB
<b>Interface Standard</b>	HDMI® 2.0, USB 2.0
<b>Maximum Resolution</b>	4096x2160@60Hz 4:4:4 8bit
<b>HDCP Support</b>	HDCP 2.2
<b>Supported Audio</b>	Analogue Stereo
<b>Separate Audio Ports</b>	2 x 3.5mm (Female)
<b>Console Number</b>	1
<b>Max Number PC/Server</b>	2
<b>Switching Method</b>	Push Button, Hotkey Switching & Software
<b>Special Features</b>	Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators
<b>Console Interfaces</b>	HDMI® Type A (Female), 2 x USB 2.0 Type A (Female), 2 x 3.5mm (Female)

42345

## 2 PORT HDMI 4K60, USB 2.0 & AUDIO CABLE KVM SWITCH

<b>PC/Server Interfaces</b>	2 x HDMI® (Male), USB 2.0 Type A (Male), 2 x 3.5mm (Male) 1.2m Integrated Cables
<b>Dimensions (approx.) WxDxH</b>	97x25x82.18mm (3.82x0.98x3.24in)
<b>Housing Material</b>	Plastic
<b>Net Weight</b>	0.436kg (0.96lb)
<b>Operating Temperature</b>	0°C - 40°C (32°F - 104°F)
<b>Storage Temperature</b>	-20°C - 60°C (-4°F - 140°F)
<b>Humidity</b>	0 - 90% RH (non-condensing)
<b>Power Requirements</b>	Via USB
<b>Colour</b>	Black