

39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER

39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER

39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER

The Lindy Cat.6 HDMI® 4K60, USB & Audio KVM Extender allow users to control a source device such as a PC from a single keyboard, mouse and display up to 70m using a Cat.6 RJ45 cable.

The following distance and resolution combinations are possible when using high quality Cat.6 or above U/UTP or F/UTP cable:70m:

1920x1080@60Hz 4:4:4 8bit

40m: 3840x2160@60Hz 4:4:4 8bit

Support for HDMI® 18G signals allows for the transmission of highly detailed 3840x2160@60Hz resolutions, perfect for detailed content in control rooms, medical setups or security installations. Ideal for KVM applications, the Extender consists of a transmitter and a receiver unit; the transmitter must be connected to a source such as a PC or KVM Switch, the console with display, keyboard and mouse must be connected to the receiver.

The extender features an HDMI® loop-through output on the transmitter which allows for simultaneous viewing using both the local and remote displays. With the EDID DIP-switch the user can copy EDID datas from the display connected to the receiver or the loop-out port, or select from presets (4K60 and 1080p). Audio signal can be de-embedded from the 3.5mm output port on the receiver to connect speakers or headphones. PoC (Power over Cable) functionality provides additional flexibility; this allows power to be supplied alongside data through Cat.6 network cable in a point-to-point connection between the two units, meaning only a single power supply is required at the transmitter or receiver unit. Ideal when power outlets are limited at the receiver end of the installation. In addition, the power supply is connected via a screw type DC jack, providing a more secure and reliable connection, perfect for professional installations where accidental disconnections could create a major issue. This extender provides a simple plug & play installation with no additional drivers required, great for both professional and first time users.

Please note: This product is not designed to be used in conjunction with active network equipment and must only be used in a point to point connection.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER



39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER

PRODUCT DETAILS

KEY FEATURES

Extends HDMI® and USB HID signals up to 70m using a single Cat.6 cable

Supports HDMI® resolutions up to 4K@60Hz 4:4:4 8bit with HDR

EDID management and HDMI® loop-out port to connect one additional display on the transmitter

Supports PoC (Power over Cable), requiring a power supply connection from only one side of the installation

2 year warranty

SPECIFICATIONS

AV Interface	HDMI®
Interface Standard	2.0, USB 1.1
Supported Bandwidth	18Gbps
Maximum Distance	70m (229.66ft)
Maximum Resolution	3840x2160@60Hz 4:4:4 8bit
HDCP Support	2.2
EDID Pass Through	DIP-switch with copy function and presets
Supported Audio	HDMI® Audio Pass-through
Separate Audio Ports	3.5mm
Transmission Medium	1 x Cat.6
Special Features	HDMI® Loop Out Port, PoC (Power over Cable), Audio de-embedding
Transmitter Input	HDMI® Type A (Female), USB Type B (Female)

39383

70M CAT.6 HDMI 4K60, USB & AUDIO KVM EXTENDER

Transmitter Output	RJ-45 (Female), HDMI® Type A (Female)
Receiver Input	RJ-45 (Female)
Receiver Output	HDMI® Type A (Female), 2 x USB Type A (Female), 3.5mm Audio (Female)
Power	5.5/2.1mm
Dimensions (approx.) WxDxH	90x68x22mm (3.54x2.68x0.87in) per unit
Housing Material	Metal
Net Weight	0.56kg (1.23lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	20 - 90% RH (non-condensing)
Power Requirements	12VDC 1A
Colour	Black
Unit	Receiver and Transmitter