


38113

# 1500M FIBRE OPTIC DVI-D SINGLE LINK EXTENDER

This fiber-optic extender allows you to transmit a DVI-D video signal up to 500 meters using a multimode duplex LC cable (50/125  $\mu\text{m}$ ) or up to 1,500 meters using a single-mode cable (9/125  $\mu\text{m}$ ).



38113

# 1500M FIBRE OPTIC DVI-D SINGLE LINK EXTENDER

## PRODUCT DETAILS

### KEY FEATURES

Extends DVI-D signals at distances of up to 1500m using a single fibre optic cable (not included)

Supports HDTV resolutions up to 1920x1200@60Hz / 1080p@60Hz

6Gbps Total Bandwidth over Single 2-core Fibre Optic Cable Link

TAA compliant

2 year warranty

### SPECIFICATIONS

<b>AV Interface</b>	DVI-D
<b>Interface Standard</b>	DVI-D 2.0 (Single Link)
<b>Supported Bandwidth</b>	4.95Gbps
<b>Maximum Distance</b>	500m (1640.4ft) - 1x LC Duplex (50/125µm); 1500m (4921.2ft) - 1x LC Duplex (9/125µm)
<b>Maximum Resolution</b>	1920x1200@60Hz
<b>Transmission Medium</b>	1 x Duplex LC (50/125µm / 9/125µm)
<b>Laser Class (only for Fibre)</b>	1
<b>Wavelength (only for Fibre)</b>	1310/1550nm
<b>Special Features</b>	Self-EDID learning
<b>Transmitter Input</b>	DVI-D (Male)
<b>Transmitter Output</b>	Duplex LC (Female)
<b>Receiver Input</b>	Duplex LC (Female)

38113

**1500M FIBRE OPTIC DVI-D SINGLE LINK EXTENDER**

<b>Receiver Output</b>	DVI-D (Male)
<b>Power</b>	3.5/1.35mm DC socket
<b>Dimensions WxDxH</b>	40x70x15mm (1.57x2.76x0.59in) per unit
<b>Housing Material</b>	Metal
<b>Net Weight</b>	0.1kg (0.22lb) per unit
<b>Operating Temperature</b>	0°C - 50°C (32°F - 122°F)
<b>Storage Temperature</b>	-20°C - 65°C (-4°F - 149°F)
<b>Humidity</b>	10 - 75% RH (non-condensing)
<b>Power Requirements</b>	5VDC <400mA per unit
<b>Colour</b>	Silver
<b>Unit</b>	Transmitter and Receiver