

38231

# 4 PORT 18G HDMI 2.0 SPLITTER WITH AUDIO EXTRACTOR

The Lindy 4 Port HDMI® 18G Splitter with Audio is a multi-function solution for distributing high quality HDMI® signals across 4 displays simultaneously from one source device, while extracting digital or analogue audio separately.

With support for resolutions up to 4K 60Hz 4:4:4 8bit, this splitter is great for creating eye-catching quad display digital signage in retail scenarios, displaying sports across multiple screens in sports bars or distributing engaging multiscreen educational presentations at tradeshow.

The splitter also has separate optical and 3.5mm audio ports to easily extract audio from HDMI® to connect non-HDMI® amplifiers or soundbars, ideal for supporting video with immersive multichannel audio.

The additional ability to cascade this splitter up to three further levels allows for an extended HDMI® splitting experience, ideal for multi-screen situations such as informational broadcasting in airports, train stations or stock exchange offices.

The splitters also feature an integrated switch to downscale the input signal to Full HD, making installations with older displays hassle free while always ensuring the viewer receives the optimum picture from their display.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc



38231

# 4 PORT 18G HDMI 2.0 SPLITTER WITH AUDIO EXTRACTOR

---



38231

# 4 PORT 18G HDMI 2.0 SPLITTER WITH AUDIO EXTRACTOR

## PRODUCT DETAILS

### KEY FEATURES

Displays HDMI® signals across 4 displays simultaneously from one source device

Supports resolutions up to 4K 60Hz 4:4:4, with additional support for HDR

Extract digital and analogue audio from HDMI® for non-HDMI® amplifiers

Features a neat switch for downscaling from 4K to 1080p

2 year warranty

### SPECIFICATIONS

AV Interface	HDMI®
Interface Standard	HDMI® 2.0
Supports Bandwidth	18Gbps
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
HDCP Support	2.2
Supported Audio	Audio Pass-through; LPCM 2CH; Up to 7.1CH (Optical)
Separate Audio Ports	3.5mm (Female); Toslink (Optical)
Special Features	Downscaler Function, EDID Emulation
Input	HDMI® Type A (Female)
Output	4 x HDMI® Type A (Female), Toslink (Optical), 3.5mm (Female)
Power	5.5/2.1mm
Dimensions (approx.) WxDxH	180x14.4x63mm (7.09x0.57x2.48in)

38231

# 4 PORT 18G HDMI 2.0 SPLITTER WITH AUDIO EXTRACTOR

---

<b>Housing Material</b>	Metal
<b>Net Weight</b>	0.122kg (0.27lb)
<b>Operating Temperature</b>	0°C - 40°C (32°F - 104°F)
<b>Storage Temperature</b>	-20°C - 60°C (-4°F - 140°F)
<b>Humidity</b>	20-90% RH (non-condensing)
<b>Power Requirements</b>	5VDC 1A
<b>Colour</b>	Black