

38321

20M FIBRE OPTIC HYBRID MICRO-HDMI 4K60 CABLE WITH DETACHABLE HDMI & DVI CONNECTORS

Lindy's range of Fibre Optic Hybrid Micro-HDMI® 4K60 cables with detachable connectors are the professional solution for extending Micro-HDMI®, HDMI® & DVI signals over longer distances, with no requirement for additional adapters. Combining the flexibility and high EMI & RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in critical AV setups or commercial installations.

Supplied as a thin cable with a premium metal, narrow Micro-HDMI connector, this can be installed easily through conduit and other small spaces with no damage caused to the internal cable structure, while the detachable HDMI® and DVI connectors can be added at the ends of the installation for connection to an even wider variety of displays and devices such as TVs, PCs or digital signage. This innovative design allows for a much wider range of connectivity solutions that can be customized freely by the user, including HDMI® to DVI, HDMI® to HDMI® or DVI to a DVI display.

Supporting all the premium features that come with the 2.0 18G specification, these cables can deliver resolutions up to 4K at 60Hz, perfect for ensuring the best possible image quality in attention grabbing retail displays, immersive AV installations at events or a premium residential setup. HDR support ensures a much wider colour gamut, greater contrasts and an enhanced brightness to provide eye catching content even in outdoor or brightly lit scenarios. Multi-channel audio support including Dolby True HD and Dolby Atmos, also provides a more encompassing audio experience for the listener, complementing the high quality video on display.

ARC function is supported up to 50m only if used with HDMI® compliant devices.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



38321

20M FIBRE OPTIC HYBRID MICRO-HDMI 4K60 CABLE WITH DETACHABLE HDMI & DVI CONNECTORS



38321

20M FIBRE OPTIC HYBRID MICRO-HDMI 4K60 CABLE WITH DETACHABLE HDMI & DVI CONNECTORS

PRODUCT DETAILS

KEY FEATURES

Combines copper and fibre optic cable for a hybrid, long distance HDMI®, Micro-HDMI® & DVI connectivity solution

Supplied as a Micro-HDMI® Male to Male cable, with detachable HDMI® & DVI connectors

Supports HDMI® 18G resolutions up to 4K@60Hz with additional support for HDR

Premium, metal connectors

2 year warranty

SPECIFICATIONS

Connector A	Micro-HDMI® Male (with Detachable DVI-D & HDMI® Connector)
Connector B	Micro-HDMI® Male (with Detachable DVI-D & HDMI® Connector)
Housing Material	Zinc Alloy
Connector Plating	Gold Plated
Pin Construction	Gold-Plated Brass
Pin Plating	Gold Plated
Micro-HDMI® Connector Dimensions (WxDxH)	44.2x12.7x7.1mm (1.74x0.5x0.28in)
HDMI® Connector Dimensions (WxDxH)	48.2x20x10mm (1.9x0.79x0.39in)
DVI Connector Dimensions (WxDxH)	43x40x14.5mm (1.69x1.57x0.57in)
Length	20m (65.62ft)
Standard	2.0
Colour	Black

38321

20M FIBRE OPTIC HYBRID MICRO-HDMI 4K60 CABLE WITH DETACHABLE HDMI & DVI CONNECTORS

Type	Round
Jack Diameter	6mm (0.24in)
Jack Material	PVC
Conductor Material	Gold Plated Copper
Conductor Gauge	24AWG
Shielding	Aluminium Mylar
Supported Bandwidth	18Gbps
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
Nominal Attenuation	-1dB~-2dB
Minimum Bend Radius	20mm (0.79in)
Operating Temperature	0°C - 50°C (32°F - 122°F)
Storage Temperature	-20°C - 85°C (-4°F - 185°F)