39540

8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

39540

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

This advanced KVM Switch has been designed for use with PCs and Macs. It features DisplayPort video ports and a two port USB 2.0 hub for connecting and sharing peripherals. With audio support, you can also connect speakers or headsets.

The switch occupies only a single 1U space in a 19_ rack and supports screen resolutions of up to 4K Ultra HD 60Hz, great for graphical content in gaming setups, video editing or controlling multiple workstations. It provides 2 simple switching modes, via keyboard hotkeys and front panel buttons.

A local console can be connected to the 2 USB and DP ports on the rear panel while the built-in 2 port USB 2.0 hub saves money on requiring additional devices by sharing peripherals between the connected computers. The unique switching arrangement allows the USB hub to be switched independently of the PCs for uninterrupted printing, scanning or external drive access. Options can be accessed only via keyboard hotkeys.

LED indicators show the status of the selected channel.

Please Note: connection cables are not included. DisplayPort, USB A to B, and 3.5mm audio cables are required for each connected computer. The maximum supported distance for USB, using standard cables, is 5m. For distances over 5m, use a Lindy USB Active Extension Cable. MST hubs are not supported.

576d6cf4-4d83-4814-971b-6c1f91323c7a.jpg b95ab0eb-6bdf-441b-aa03-4d7051467a6b.jpg ad74867b-7487-4c4d-b10d-89e69a

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

39540

8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

- Supports up to 8 USB, DisplayPort & Audio equipped computers
- Supports DisplayPort 1.2 resolutions up to 4K 60Hz
- Built in 2 ports USB 2.0 Hub for sharing additional peripherals
- Port switching via hotkey or front panel buttons
- 2 year warranty

SPECIFICATIONS

AV Interface	DisplayPort
Console Interfaces	USB
Interface Standard	DisplayPort 1.2, USB 2.0
Maximum Resolution	3840x2160@60Hz 4:4:4 8bit
HDCP Support	1.4
Supported Audio	Analogue Stereo
Separate Audio Ports	3.5mm (Female)
Console Number	1
Max Number PC/Server	8
Switching Method	Port buttons, Hotkey (configurable)
19" Rack Mountable	Yes (1U - Rack Mount Brackets included)
Console Interfaces	DisplayPort (Female), 2 x USB Type A HID (Female), 3.5mm (Female)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

39540

8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

PC/Server Interfaces	8 x DisplayPort (Female), 8 x USB 2.0 Type B (Female), 8 x 3.5mm (Female)
Other Interfaces	2 x USB 2.0 Type A (Female) shared ports (front panel)
Power	5.5/2.1mm DC
Dimensions (approx.) WxDxH	300x164x44mm (11.81x6.46x1.73in)
Housing Material	Metal
Net Weight	1.53kg (3.37lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	5~90% RH (non-condensing)
Power Requirements	9VDC 2A
Colour	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it