

39540

# 8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.

This advanced KVM Switch has been designed for use with PCs and Macs. It features DisplayPort video ports and a two port USB 2.0 hub for connecting and sharing peripherals. With audio support, you can also connect speakers or headsets.

The switch occupies only a single 1U space in a 19" rack and supports screen resolutions of up to 4K Ultra HD 60Hz, great for graphical content in gaming setups, video editing or controlling multiple workstations. It provides 2 simple switching modes, via keyboard hotkeys and front panel buttons.

A local console can be connected to the 2 USB and DP ports on the rear panel while the built-in 2 port USB 2.0 hub saves money on requiring additional devices by sharing peripherals between the connected computers. The unique switching arrangement allows the USB hub to be switched independently of the PCs for uninterrupted printing, scanning or external drive access. Options can be accessed only via keyboard hotkeys.

LED indicators show the status of the selected channel.

Please Note: connection cables are not included. DisplayPort, USB A to B, and 3.5mm audio cables are required for each connected computer. The maximum supported distance for USB, using standard cables, is 5m. For distances over 5m, use a Lindy USB Active Extension Cable. MST hubs are not supported.



39540

# 8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

---



39540

# 8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

## PRODUCT DETAILS

### KEY FEATURES

Supports up to 8 USB, DisplayPort & Audio equipped computers

Supports DisplayPort 1.2 resolutions up to 4K 60Hz

Built in 2 ports USB 2.0 Hub for sharing additional peripherals

Port switching via hotkey or front panel buttons

2 year warranty

### SPECIFICATIONS

<b>AV Interface</b>	DisplayPort
<b>Console Interfaces</b>	USB
<b>Interface Standard</b>	DisplayPort 1.2, USB 2.0
<b>Maximum Resolution</b>	3840x2160@60Hz 4:4:4 8bit
<b>HDCP Support</b>	1.4
<b>Supported Audio</b>	Analogue Stereo
<b>Separate Audio Ports</b>	3.5mm (Female)
<b>Console Number</b>	1
<b>Max Number PC/Server</b>	8
<b>Switching Method</b>	Port buttons, Hotkey (configurable)
<b>19" Rack Mountable</b>	Yes (1U - Rack Mount Brackets included)
<b>Console Interfaces</b>	DisplayPort (Female), 2 x USB Type A HID (Female), 3.5mm (Female)

39540

# 8 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO KVM SWITCH

<b>PC/Server Interfaces</b>	8 x DisplayPort (Female), 8 x USB 2.0 Type B (Female), 8 x 3.5mm (Female)
<b>Other Interfaces</b>	2 x USB 2.0 Type A (Female) shared ports (front panel)
<b>Power</b>	5.5/2.1mm DC
<b>Dimensions (approx.) WxDxH</b>	300x164x44mm (11.81x6.46x1.73in)
<b>Housing Material</b>	Metal
<b>Net Weight</b>	1.53kg (3.37lb)
<b>Operating Temperature</b>	0°C - 40°C (32°F - 104°F)
<b>Storage Temperature</b>	-20°C - 60°C (-4°F - 140°F)
<b>Humidity</b>	5~90% RH (non-condensing)
<b>Power Requirements</b>	9VDC 2A
<b>Colour</b>	Black