41072

15M ACTIVE HDMI 4K60 CABLE

41072

Lindy_s Active HDMI® 18G cables combine sleek, modern design with superior performance to provide high quality, reliable HDMI® transmission over long distances. Lindy's range of active cables come with an in-built chipset that amplifys the users signal to create a much longer HDMI® transmission that isnt possible with standard passive HDMI® cables, while also avoiding the need for additional expensive extenders or repeaters. With the active chipset built discreetly into the stylishly designed headshell, these cables can easily be installed through conduit or tighter spaces. These premium cables also support the full 18G HDMI® bandwidth to display 4096x2160@60Hz resolutions with additional support for the REC.2020 colour space that covers the wider colour gamut required for high-dynamic range content, for enhanced contrast and more lifelike colour.

Complying to the HDMI® 2.0 cable specification, these cables are ideal for use with a variety of source devices including set-top boxes, HDMI® media players or PCs when connected to modern displays or projectors. Perfect for use in eye-catching retail displays, informational digital signage or immersive video playback in sports bars, music venues or high end home cinemas.

With support for a range of multi-channel audio formats, including Dolby True HD and DTS-HD Master Audio, these cables also ensure an impressive three-dimensional surround sound performance when connected to an amplifier's speaker system. CEC functionality also allows many of the source device's settings to be controlled via the display or projectors controls to provide a simple and effective control solution, while avoiding the necessity for several remote controls.

Lindy's active cables should be connected in accordance with the instructions for the optimum experience. The connector marked _display_ must be connected to the monitor or screen. Failure to connect the cable in the correct manner will result in no signal. Some projectors have recessed HDMI® sockets, please ensure they can accommodate the connector used on this cable.

Active HDMI® cables cannot be connected together or _daisy chained_.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

906b62b5-15b4-4773-9c44-18600ca24eac.jpg

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

41072

15M ACTIVE HDMI 4K60 CABLE

PRODUCT DETAILS

KEY FEATURES

- Creates a long distance HDMI® connection between a 4K source device and display
- Delivers reliable 4K@60Hz resolutions over longer cable distances
- Active HDMI® technology built into the connector for flexible installation
- Full support for HEC, ARC and CEC compliant devices
- 2 year warranty

SPECIFICATIONS

Connector A	HDMI® Type A Male
Connector B	HDMI® Type A Male
Housing Material	ABS
Connector Plating:24K Gold Flash	
Pin Construction	Phosphor Bronze
Pin Plating	24K Gold 3µm
Dimensions WxDxH (approx.)	21.68x43x13.22mm (0.85x1.69x0.52in)
Length	15m (49.21ft)
Standard	2.0
Colour	Black
Type	Round
Jacket Diameter	8mm (0.31in)
Jacket Material	PVC
Conductor Material	Bare Copper

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

41072

15M ACTIVE HDMI 4K60 CABLE

Conductor Gauge	26AWG
Shielding	Aluminium Foil Mylar, 100% / Aluminium Alloy Braiding, 70%
Supported Bandwidth	18Gbps
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
Nominal Attenuation	300KHz~825MHz <5dB; 2.475GHz~4.125GHz 12dB-20dB
Minimum Bend Radius	100mm (3.94in)
Operating Temperature	-20°C - 80°C (-4°F - 176°F)
Storage Temperature	-10°C - 60°C (14°F - 140°F)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it