


42344

2 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO CABLE KVM SWITCH

The Lindy 2 Port DisplayPort 1.2, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over two DP equipped PCs from a single keyboard, mouse and monitor. With integrated cables, this switch can be easily connected directly to the system, with no need for purchasing additional cables and saving time on the installation.

Support for resolutions up to 4K Ultra HD 60Hz ensures the optimum image quality, perfect for high graphical content in gaming setups, video editing or dual system control workstations. The audio output port on the main unit also allow users to connect headphones or speaker to add immersive 2CH audio and a microphone, while additional USB peripherals can be integrated with a USB hub.

The KVM switch features multiple switching options including a push button control (with 1.5m cable), hotkey and software switching to provide simple, reliable control for the user, great for both professional and first time users.



42344

2 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO CABLE KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

Control two DisplayPort equipped PCs from a single keyboard, mouse and monitor

Switch via the unit's push button control, software or keyboard hot keys

Supports DisplayPort 1.2 signals, up to 4K 60Hz

Integrated cables for quick, hassle-free installation

2 Year Warranty

SPECIFICATIONS

AV Interface	DisplayPort
Console Interfaces	USB
Interface Standard	DisplayPort 1.2, USB 2.0
Maximum Resolution	4096x2160@60Hz 4:4:4 8bit
HDCP Support	HDCP 1.4
Supported Audio	Analogue Stereo
Separate Audio Ports	2 x 3.5mm (Female)
Console Number	1
Max Number PC/Server	2
Switching Method	Push Button, Hotkey Switching & Software
Special Features	Supports USB 2.0 Hubs And Device Sharing, Active LED Indicators
Console Interfaces	DisplayPort (Female), USB 2.0 Type A (Female), 2 x 3.5mm (Female)

42344

2 PORT DISPLAYPORT 1.2, USB 2.0 & AUDIO CABLE KVM SWITCH

PC/Server Interfaces	2 x DisplayPort (Male), USB 2.0 Type A (Male), 2 x 3.5mm (Male) 1.2m Integrated Cables
Dimensions (approx.) WxDxH	97x25x82.18mm (3.82x0.98x3.24in)
Housing Material	Plastic
Net Weight	0.433kg (0.95lb)
Operating Temperature	0°C - 40°C (32°F - 104°F)
Storage Temperature	-20°C - 60°C (-4°F - 140°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	5V
Colour	Black