43406

# 4X4 USB 3.2 GEN 1 MATRIX SWITCH

43406

The Lindy USB 3.2 Gen 1 Matrix Switch allows the user to share up to 4 USB devices to up to 4 hosts in many different ways: by pushing the buttons on the front panel, via web GUI and using RS-232 commands.

It's possible to save up to 8 preset configurations, change the name of hosts and devices from the GUI and with the commands, for smooth and easy operations.

This matrix switch is ideal for sharing printers, storage devices or webcam in office environments, for conference room presentation systems, KVM or industrial applications. It can support USB 3.2 Gen 1 with data transfer rates up to 5Gbps, USB 2.0 and USB 1.1 devices, perfect for use with multiple PCs or Macs.

Each USB Type-A port provide up to 900mA power to the connected device.

Information about USB 3.0, 3.1 & 3.2

USB 3.0, USB 3.1 and USB 3.2 PCs, cables and devices are all compatible with each other, when using either a USB Type A or USB Type C host interface.

USB 3.0, USB 3.1 Gen 1 and USB 3.2 Gen 1 all support data transfer rates up to 5 Gbps.

USB 3.1 Gen 2 and USB 3.2 Gen 2 both support data transfer rates up to 10 Gbps.

59567fc9-a808-4c21-a711-634001260009.jpg c9bf6a40-b173-4c3a-8113-42204c74e6fb.jpg 612aa6f8-f495-4622-8d7f-a347da9

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

43406

# 4X4 USB 3.2 GEN 1 MATRIX SWITCH

## PRODUCT DETAILS

### KEY FEATURES

- Supports USB 3.2 Gen 1 (USB 3.0), USB 2.0/1.1 backwards compatibility
- Switching between computers with buttons, TCP/IP with web GUI or RS-232 commands
- Matrix switch with presets function
- Plug & Play, no software required
- 2 year warranty

### SPECIFICATIONS

| | |
|---|---|
| **USB Standard** | USB 3.2 Gen 1 |
| **Supported Bandwidth** | 5 Gbps |
| **Chipset** | AT32F437 + VL817 |
| **Compatibility** | USB equipped computers |
| **Power Delivery** | 900mA on each USB Type A port |
| **Special Features** | Switching by buttons; web GUI, RS-232 commands |
| **Inputs** | 4 x USB 3.0 Type B (Female) |
| **Outputs** | 4 x USB Type A (Female) |
| **Control ports** | RJ-45 (Female), RS-232 3-Pin Terminal Block |
| **Power** | 5.5/2.5mm |
| **Dimensions WxDxH** | 221x105x26mm (8.7x4.13x1.02in) |
| **Housing Material** | Metal |
| **Net Weight** | 1.15kg (2.54lb) |
| **Operating Temperature** | 0°C - 40°C (32°F - 104°F) |

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

43406

# 4X4 USB 3.2 GEN 1 MATRIX SWITCH

| | | |
|---|---|---|
| **Storage Temperature** | -20°C - 60°C (-4°F - 140°F) | |
| **Humidity** | 0 - 90% RH ( non-condensing) | |
| **Power Requirements** | | 12V 3A |
| **Colour** | | Black |

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it