

70436

## 2 PORT AUTOMATIC OPTICAL AUDIO SWITCH

The Lindy 2 Port Automatic Optical Audio Switch allows users to connect two digital optical Toslink sources to a single optical TosLink (SPDIF) input on an AV amplifier, Hi-Fi or home cinema system. The optical switch will automatically detect the live signal and switch to this channel.

Ideal for use with games consoles, HD players, set top boxes, PC\_s etc. and saves on wear and tear of constant plugging and unplugging of cables.

Please note: TosLink cables are not included.



70436

# 2 PORT AUTOMATIC OPTICAL AUDIO SWITCH

## PRODUCT DETAILS

### KEY FEATURES

Connects two digital optical Toslink sources to a single optical Toslink input

Automatic or manual switch function

Input ports: 2 x Toslink (Optical Fibre)

Output Ports: 1 x Toslink (Optical Fibre)

2 year warranty

### SPECIFICATIONS

<b>AV Interface</b>	TosLink
<b>Supports Bandwidth</b>	32 - 96kHz
<b>Supported Audio</b>	Uncompressed PCM / LPCM, Dolby AC-3, Dolby 5.1, Dolby Digital and DTS
<b>Special Features</b>	Automatic switching of active ports
<b>Input</b>	2 x TosLink (Optical Fibre)
<b>Output</b>	1 x TosLink (Optical Fibre)
<b>Power</b>	5.5/2.1mm DC socket
<b>Dimensions (approx.) WxDxH</b>	75x65x30mm (2.95x2.56x1.18in)
<b>Housing Material</b>	Plastic
<b>Net Weight</b>	0.055kg (0.12lb)
<b>Operating Temperature</b>	0°C - 50°C (32°F - 122°F)
<b>Storage Temperature</b>	-20°C - 70°C (-4°F - 158°F)
<b>Humidity</b>	20 - 80% RH (non-condensing)
<b>Power Requirements</b>	5VDC 1.2A

70436

# 2 PORT AUTOMATIC OPTICAL AUDIO SWITCH

Colour

Black