32810

4 PORT HDMI 18G, USB 2.0 & AUDIO KVM SWITCH

32810


A KVM switch allows an operator to conveniently control and manage multiple devices, such as PCs and servers, from a single keyboard, mouse and display console.


The Lindy 4 Port HDMI® 4K60, USB 2.0 & Audio KVM Switch is a compact solution for providing access and control over four HDMI equipped PCs from a single keyboard, mouse and monitor setup.

Support for resolutions up to 4K Ultra HD 60Hz ensures the highest image quality, perfect for demanding graphical content in gaming setups, video editing or quad system control workstations. The additional support for High-Dynamic Range ensures video content can be seen with enhanced brightness, greater contrasts and a much wider colour gamut. The audio output ports on the main unit also allow users to connect headphones or speakers to add immersive 2CH audio and a microphone, pressing the Audio On/Off button on the front panel mutes these devices. These ports are not connected to the HDMI® signal but to a built-in USB converter while an additional USB device such as a printer, scanner or hard drive can be connected to the additional USB port on the front panel.

The KVM switch features two switching options including push buttons on the unit and keyboard hotkeys provide simple, reliable control for the user, great for both professional and first time users.

ca0520d8-d9ea-4320-a65f-96503ba17339.jpg





Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

32810

4 PORT HDMI 18G, USB 2.0 & AUDIO KVM SWITCH

PRODUCT DETAILS

KEY FEATURES

- Controls four HDMI® equipped PCs from a single keyboard, mouse and monitor
- Switch via the unit's push button or keyboard hotkeys
- Supports HDMI® 18G resolutions up to 4K@60Hz 4:4:4 with HDR
- 3.5mm stereo audio ports to connect microphone, speakers or headphones
- 2 year warranty

SPECIFICATIONS

AV Interface	HDMI®
Console Interfaces	USB
Interface Standard	HDMI® 2.0, USB 2.0
Maximum Resolution	4096x2160@60Hz 4:4:4 8Bit
HDCP Support	2.2
Supported Audio	Analogue Stereo
Separate Audio Ports	2 x 3.5mm (Female)
Console Number	1
Max Number PC/Server	4
Switching Method	Push Button, Hotkey Switching
Special Features	USB 2.0 device port, Audio ports with On/Off button, Active LED Indicators
Console Interfaces	HDMI® Type A (Female), 3 x USB 2.0 Type A (Female), 2 x 3.5mm (Female)

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

32810

4 PORT HDMI 18G, USB 2.0 & AUDIO KVM SWITCH

PC/Server Interfaces	4 x HDMI® Type A (Female), 4 x USB 2.0 Type B (Female)
Power	3.5/1.35mm DC socket
Dimensions (approx.) WxDxH	231x108x23mm (9.09x4.25x0.91in)
Housing Material	Metal
Net Weight	0.689kg (1.52lb)
Operating Temperature	0°C - 50°C (32°F - 122°F)
Storage Temperature	-10°C - 60°C (-14°F - 140°F)
Humidity	5 - 80% RH (non-condensing)
Power Requirements	5VDC 2A
Colour	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it