GeoTag DIN Rail

DIN RAIL GPS TRACKER PLUS 1 YEAR OF GPS TRACKING PLATFORM SUBSCRIPTION

Power distribution units and generators are often stationary or hidden inside larger systems. If one goes missing or is moved unexpectedly, finding it can be slow, costly, and disruptive.

GeoTag DIN Rail installs directly into your existing DIN-mounted infrastructure, giving you **live GPS data without extra boxes, cables, or mounts**. Always powered when your system is running, it also has a backup battery so tracking continues during downtime or transport.

Ideal for generator hire companies, event power suppliers, and industrial rack setups, it’s a **set-and-forget solution** that blends seamlessly into your existing equipment.

GeoTag DIN Rail

7af4066d-1b99-42bd-ac9c-a9d371f1f2c3.png

43f03751-6ab6-4b2f-909c-952edeb319f1.png

b4abcda8-13da-47a0-94eb-842e88

1e2e54fd-b2cb-41c5-9a5b-2d7aaaad6a81.png

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GeoTag DIN Rail

DIN RAIL GPS TRACKER PLUS 1 YEAR OF GPS TRACKING PLATFORM SUBSCRIPTION

PRODUCT DETAILS

KEY FEATURES

- DIN-rail mounted GPS tracker for Power Distros, Industrial Racks, and Generators
- Industrial-grade tracking, right inside your power systems
- Integrated backup battery for continuous tracking during downtime or transport
- Supports both 12V and 24V voltage input levels (adaptor may be required)
- Standard 2-module DIN rail

SPECIFICATIONS

Dimensions	90 × 36 × 58 mm
Weight	154g
Mount Type	DIN Rail Mounted 2 module unit
LED Indicators	Red = Power, Orange = GSM, Blue = GPS
Certifications	RoHS, CE, UKCA
Power Input	100-260V 50-60Hz
Battery Type	Lithium Ion
Battery Capacity	1800 mAh
Runtime	10 days @10-min intervals, 5–7 days under continuous motion
Daily Usage	~142 mAh
Power Adaptor	N/A
SIM	2G + 4G

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

GeoTag DIN Rail

DIN RAIL GPS TRACKER PLUS 1 YEAR OF GPS TRACKING PLATFORM SUBSCRIPTION

Connectivity	GSM/GPRS & LTE modules with 170+ country global SIM
Location Capture	GPS & A-GPS
GPS Accuracy	<10m (outdoor)
Location Update Intervals	Configurable 1 min – 120 min; motion-sensitive sleep feature
Temperature Range	–20 °C to +45 °C
Humidity Range	20–95 % humidity

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it