32622

4 PORT IPOWER SWITCH

32622

The Lindy IPower Switch is a compact and intelligent power management solution designed for IT, AV, industrial, and small office environments. It connects to a network infrastructure to provide remote control and monitoring of up to four connected devices such as servers, workstations, hubs, and routers. Users can easily perform power-on, power-off, and reboot functions either through a user-friendly web interface or external control commands.


Each output can be individually configured with power-on and power-off delay settings, allowing precise sequencing after a power outage or system reset.
Supports total power of 2500W, A current range from 0A to 10A with a Voltage range from 110V to 250V.


Each outlet has its own status indication LED and button to allow the manual management function (not active by default). From the web GUI it is possible to manage the complete configuration of the unit, monitor the status of each outlet port, schedule on/off status and so on. Open APIs for Telnet, Modbus TCP, SSH, SNMP and MQTT protocols are supported, while security and network settings are provided to cover most of the requirements needed in demanding applications.

The user can also configure email notifications to receive alerts and reports directly, including warnings about overload and overcurrent thresholds.

Ideal for IT administrators, system integrator, and AV installers, the Lindy IPower Switch delivers reliable, flexible, and secure power control for critical applications.

574f98bb-7ebb-46a0-814d-5f367e596e5e.jpg





Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

32622

4 PORT IPOWER SWITCH

PRODUCT DETAILS

KEY FEATURES

- Remote power management switch for up to 4 devices
- Control via intuitive web GUI, RS232 and API commands
- Individual power control and monitoring (voltage, current and consumption)
- Scheduler
- Email server
- Power-on and power-off delay
- Overcurrent and overvoltage protection
- Power-off memory
- Support Telnet, Modbus TCP, SSH, SNMP and MQTT protocols
- 3 years warranty

SPECIFICATIONS

Input Voltage	110-250V 50/60Hz 10A
Switched Power (total)	max. 2500W
Voltage Range	110-250V
Nominal Input Frequency	45-65Hz
Current Range	0A-10A
No-load power consumption	1.53W
LED indicators	
Input	IEC C14
Output	4x IEC C13

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

32622

4 PORT IPOWER SWITCH

Network Connection	2xRJ45 redundant Ethernet ports
Control	RS-232 3-pin phoenix
Dimensions (approx.) WxDxH	218x153x42.5mm (8.58x6.02x1.67in)
Housing Material	Metal
Net Weight	1.7kg (3.75lb)
Operating Temperature	-10-55°C (14°F-131°F)
Storage Temperature	-20-70°C (-4°F-158°F)
Humidity	0-95% (non-condensing)
Colour	Black

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it