

38330

9 PORT HDMI 4K30 MULTI-VIEW SWITCH

HDMI® Multi-view switches are professional solutions for showing one or more sources of HDMI® content on a single display.

The Lindy HDMI® 4K30 Multi-view Switch is a high performance solution for switching between a single or multiple HDMI® source devices and outputting to a single HDMI® display or projector. As well as standard switching between up to 9 devices, content can be viewed from all connected devices in a variety of layouts in the display, ideal for a wide range of scenarios.

These scenarios include the connection of two source devices in split screen layouts, which provide a useful layout for small scale CCTV or supporting content in retail stores, to the connection of 9 inputs for use in traffic monitoring or TV broadcasting facilities.

Resolutions up to 4K UHD 3840x2160@30Hz are supported providing an optimum viewing experience in detailed digital signage, security or broadcasting installations.

Switching can be easily controlled by the user via the push button on the main unit, or using the IR remote control, which also allows for hassle free switching between layouts modes. The switch also allows for output resolution scaling to ensure a consistent image quality within a setup, as well as independent audio switching from the connected HDMI® devices, great for adding music or alternative commentary to video content from a separate HDMI® source. Both features can also be easily controlled using the IR remote. RS-232 serial switching can also be used for control via a PC connection.

Seamless switching guarantees there is almost no downtime when alternating between connections, ensuring there is no interruption of content, meaning nothing is missed by the viewer when experiencing live sports or breaking news headlines.



38330

9 PORT HDMI 4K30 MULTI-VIEW SWITCH



38330

9 PORT HDMI 4K30 MULTI-VIEW SWITCH

PRODUCT DETAILS

KEY FEATURES

Connects 9 HDMI® inputs and view on a single HDMI® display

Supports resolutions up to 3840x2160@30Hz 4:4:4 8bit

Simple switching via push button, IR remote or RS-232

Seamless switching between sources

2 year warranty

SPECIFICATIONS

AV Interface	HDMI®
Interface Standard	HDMI® 1.4
Supports Bandwidth	10.2Gbps
Maximum Resolution	3840x2160@30Hz 4:4:4 8bit
HDCP Support	1.4
Supported Audio	HDMI® Audio Pass-through
IR Support	38KHz
Serial Interface	RS-232
Special Features	Seamless Switching
Input	9 x HDMI® Type A (Female)
Output	HDMI® Type A (Female)
Control	RS-232 Terminal Blocks (Female)
Power	5.5/2.1mm
Dimensions (approx.) WxDxH	252x25x105mm (9.92x0.98x4.13in)

38330

9 PORT HDMI 4K30 MULTI-VIEW SWITCH

Housing Material	Metal
Net Weight	1.1kg (2.43lb)
Operating Temperature	-15°C - 55°C (5°F - 131°F)
Storage Temperature	-15°C - 55°C (5°F - 131°F)
Humidity	0 - 90% RH (non-condensing)
Power Requirements	12VDC 2A
Colour	Black