


KX12 I

PASSIVE 12" POINT SOURCE COAX SPEAKER WITH EBS TECHNOLOGY, BLACK

The Dragon-KX12 MKI is a radical reinterpretation of a coaxial point source speaker, featuring a 12" woofer and a 1.7" compression driver. Designed to deliver highquality audio, it performs with remarkable versatility, whether used as a powerful point source or as part of a line array. The MKI version introduces a sleek stainless steel chassis with a compact and lightweight design, perfect for both durability and ease of installation. The KX12 MKI rises to the challenges of high intensity applications, such as DJ monitoring in exclusive venues. Its fixed waveguide can be easily rotated by unscrewing, optimizing sound dispersion and ensuring superior performance. When used in an array, the speaker fully leverages EBS (Electronic Beam Steering) technology for precise, electronically adjustable coverage, offering consistent and controlled sound distribution. All KX12 MKI components are designed and custommade by K-array's R&D department, adhering to the company's stringent quality control standards.



KX12 I

PASSIVE 12" POINT SOURCE COAX SPEAKER WITH EBS TECHNOLOGY, BLACK

HIGHLIGHTS



POWERFUL POINT SOURCE ELEMENT

Optimized directivity, designed for standalone use or array configurations.

EBS CONTROL

When used in arrays, it supports EBS (Electronic Beam Steering) technology, enabling precise electronic control of dispersion. Each unit contributes to a focused, coherent coverage, minimizing reflections and ensuring consistent SPL across the listening area. This makes the KX12 I ideal for applications requiring high intelligibility, accurate coverage, and clean integration.



KX12 I

PASSIVE 12" POINT SOURCE COAX SPEAKER WITH EBS TECHNOLOGY, BLACK

COAXIAL DESIGN

The coaxial design provides fast transient response and consistent dispersion, ideal for precise near-field applications.



KX12 I

PASSIVE 12" POINT SOURCE COAX SPEAKER WITH EBS TECHNOLOGY, BLACK

PRODUCT DETAILS

KEY FEATURES

Simplified rigging with dedicated hardwares

Various array configurations and EBS-controlled emission

IP54 rating

Chrome/Black horn color available

Cabinet available in custom RAL colors

SPECIFICATIONS

Type	Passive point source
Transducers	12" woofer + 1.7" coaxial compression driver
Frequency Response	120 Hz - 18 kHz (-6 dB, with dedicated preset)
Max SPL	133 dB peak
Coverage	V. 40° H. 60° rotatable with screws
Power Handling	800 W
Nominal Impedance	8 ?
Connectors	2x SpeakOn NL4 1+ 1- (signal); 2+ 2- (through)
Material	Stainless steel
Colors	Black, Custom RAL
IP rating	IP54
Dimensions (WxHxD)	350x350x203 mm (13.8 x 13.8 x 8 in)

KX12 I

PASSIVE 12" POINT SOURCE COAX SPEAKER WITH EBS TECHNOLOGY, BLACK

Weight

15kg (33.1 lb)