

2777200114

FH1 PROFESSIONAL MONITORING HEADPHONES, BLACK

Experience every nuance of your track with the Fender FH1 Professional Monitoring Headphones. A perfect fit for any size studio or jam space, the FH1 headphone's closed-back design and comfort soft earpads offer exceptional passive isolation for tracking guitar, vocals, overdubs, and editing on the go without interference or headphone bleed. Each 45mm dynamic neodymium driver produces a wide, balanced sound with accurate low end, clear mids, and detailed highs across a full 10 Hz to 26 kHz frequency response.

These headphones play audio loud and clear from interfaces, laptops, mixers, and phones alike thanks to their 40 ohm impedance and 1,800 mW total power handling (900 mW per channel), making them the go to for listening to your music in full detail. Whether you're laying down tracks, mixing your next release, or just rediscovering your favorite records, the FH1 headphones pair reference-grade sound with player-focused comfort for hours of fatigue-free listening.



WwP0KcQSLFIpm1784212312_2777200114_fen_aud_dtl_1_nr.png

55smgTvx869yZgs1784212312_2777200114_fen_aud_dtl_2_nr.png

avZUAzvBddp8Us1784212312_2777200114_fen_aud_dtl_5_nr.png

2777200114

FH1 PROFESSIONAL MONITORING HEADPHONES, BLACK

PRODUCT DETAILS

KEY FEATURES

- High accuracy monitoring headphones for full music immersion
- 45mm, high-resolution neodymium drivers produce balanced sound
- Extended bass response and tuned acoustic chamber provides full picture audio
- Closed-back, over-ear design for superior passive noise isolation during tracking
- Rotating earcups with comfortable, long-lasting ear pads
- Screw-locking, gold-plated 1/4" (6.35 mm) adapter and soft carry pouch included
- Color: Black

SPECIFICATIONS

Headphone Frequency Response	10 Hz to 26 kHz
Headphone Maximum Power	1800 mW
Headphone Rated Impedance	40?
Headphone Sensitivity	98 dB SPL (1 mW)
Driver Type	45 mm, Neodymium
ncluded Accessories	1/8" to 1/4" (3.5 to 6.3 mm) Gold-Plated Screw-On Adapter Storage Bag