

NAC3MM-1

CBC COUPLER FOR LINKING POWER CABLES WITH NAC3FXXA/B CONNECTORS

powerCON NAC3MPXXA (power in) - powerCON
NAC3MPXXB (power out), CBC coupler for linking power
cables with NAC3FXXA/B.

NAC3MM-1

kUE2wRqbTYBV9IS1783953018_16995-NAC3MM-1 - rear view - 202210.png

NAC3MM-1

CBC COUPLER FOR LINKING POWER CABLES WITH NAC3FXXA/B CONNECTORS

PRODUCT DETAILS

KEY FEATURES

Reliable power cable linking – Couples powerCON power-in (NAC3FXXA) and power-out (NAC3FXXB) cable connectors for secure AC power cable extensions

Circuit Breaking Capability (CBC) – Designed for use with powerCON XX Series connectors, allowing safe connection and disconnection under load when used as specified

Robust Quick Lock design – Features Neutrik's secure Quick Lock mechanism, rated for 16 A / 250 V AC and over 1,000 mating cycles for dependable professional use

SPECIFICATIONS

Connection Type	Adapter
Contact resistance	? 3 m?
Dielectric strength	4 kVdc
Insulation resistance	> 0.1 G? (after damp heat test IEC 68-2-30)
Rated current per contact	16 A rms
Rated voltage	250 V ac
Lifetime	> 1000 mating cycles
Locking device	Quick Lock
Contact plating	2 µm Ag
Locking element	Steel Ck67
Shell	Polyamide (PA 6.6 30 % GR)
Contacts	Bronze (CuNi1Si0.2)

NAC3MM-1

CBC COUPLER FOR LINKING POWER CABLES WITH NAC3FXXA/B CONNECTORS

Flammability	UL 94 V-0
Protection class	IP 20 (mated)
Safety Requirements	EN/IEC 61984
Solderability	Complies with IEC 68-2-20
Temperature range	-30 °C to +80 °C