

NAC3MPXXB

POWERCON XX SERIES GREY OUTPUT CONNECTOR - 3/16" FLAT TAB TERMINALS

Appliance outlet connector, 3/16" flat tab terminals, grey

NAC3MPXXB

The powerCON XX is a locking mains connector. It replaces appliance couplers wherever a very reliable solution in combination with a locking device is needed in order to guarantee a safe power connection.

This connector is suitable to be used as part of fire enclosures according to IEC 62368-1

This appliance coupler fulfils the requirements of the IEC 60320-1 and of the UL 60320-1 with breaking capacity (CBC).

Appliance couplers have superior electrical endurance due to its CBC design according to the IEC 60320-1.

Appliance couplers NAC3MPXXA and NAC3MPXXB are designed to be engaged or disengaged in normal use when live or under load when using with connectors and plug connectors of the FXX Serie(s).

NAC3MPXXB

POWERCON XX SERIES GREY OUTPUT CONNECTOR - 3/16" FLAT TAB TERMINALS

PRODUCT DETAILS

KEY FEATURES

Lockable single phase connector

Certified according to IEC 60320-1 & UL 60320-1 UL US 498 / UL CA 498

Certified according to UL-1977, & CAN/CSA-C22.2 No. 182.3

Extremely robust and reliable

UL94 V-0 materials

Drop-in replacement for NAC3MXXB; mates to NAC3FXXB cable connectors

3 contacts for line, neutral and pre-mating safety ground

Fast and easy twist lock latching system Power-in (blue) and power-out (grey) versions with different keying to avoid the possibility of intermating

Suitable for fire enclosures according. to IEC 62368-1

SPECIFICATIONS

Gender	Male
Contact resistance	? 2 m?
Dielectric strength	4 kVdc / 2.8 kVac
Insulation resistance	> 1 G? (after damp heat test IEC 68-2-30)
Number of electrical contacts	2 + PE
Rating Europe	EN 60320-1: 16 A 250 V AC

NAC3MPXXB

POWERCON XX SERIES GREY OUTPUT CONNECTOR - 3/16" FLAT TAB TERMINALS

Rating USA / Canada	cUL 60320-1: 20 A 127 V AC; UL USA 498: 20 A 127 V AC; UL CA 498: 20 A 127 V AC; UL 1977: 20 A 250 V AC
Lifetime	> 5000 mating cycles
Wiresize	2,5 mm ²
Wiresize	12 AWG
Contact plating	Ag
Locking element	Stainless steel
Shell	Polyamide (PA 6.6)
Contacts	Copper Alloy
Flammability	UL 94 V-0
Protection class	IP 20
Temperature range	-30 °C to +80 °C