

NC3FXX-BAG

3 POLE FEMALE XLR CABLE CONNECTOR WITH BLACK METAL HOUSING AND SILVER CONTACTS

3 pole female cable connector with black metal housing and silver contacts.

NC3FXX-BAG

The next generation of the worldwide accepted standard of XLR cable connectors. The successor of the X series offers several new features which make it more reliable, easier to assemble and improves contact integrity as well cable strain relief.

NC3FXX-BAG

3 POLE FEMALE XLR CABLE CONNECTOR WITH BLACK METAL HOUSING AND SILVER CONTACTS

PRODUCT DETAILS

KEY FEATURES

Unique cage design of female contact for low contact resistance and high integrity

Female contact incorporates a solder barrier to prevent solder running into the contact mating area

Female connector with improved solid metal latch which is larger and easier to handle

Additional ground spring contacts for better shell ground continuity

Improved chuck type strain relief provides higher pull-out force and makes assembly easier and faster

Boot with polyurethane gland gives high protection to cable bending stresses

Colored rings and boots available for coding or identification

Sleek and ergonomic design - valuable and handy

Rugged zinc diecast shell, longlasting and dependable

Internal thread on shell is well protected against any damage

SPECIFICATIONS

Connection Type	XLR
Gender	Female
Capacitance between contacts	? 4 pF
Contact resistance	? 3 m?
Dielectric strength	1,5 kVdc
Insulation resistance	> 10 G? (initial)
Rated current per contact	16 A

NC3FXX-BAG

3 POLE FEMALE XLR CABLE CONNECTOR WITH BLACK METAL HOUSING AND SILVER CONTACTS

Rated voltage	< 50 V
Cable O.D.	3.5 - 8.0 mm
Insertion force	? 20 N
Withdrawal force	? 20 N
Lifetime	> 1000 mating cycles
Wiresize	max. 2.5 mm ²
Wiresize	max. 14 AWG
Wiring	Solder contacts
Locking device	Latch lock
Boot	Polyurethane
Contact plating	2 µm Ag
Contacts	Bronze (CuSn8)
Insert	Polyamide (PA66)
Locking element	Zinc diecast (ZnAl4Cu1) / Ck 67 (spring)
Locking element plating	Nickel
Shell	Zinc diecast (ZnAl4Cu1)
Shell coating	Black KTL
Strain relief	Polyacetal (POM)
Flammability	UL 94 V-0
Standard compliance	IEC 61076-2-103
Protection class	IP 40
Solderability	Complies with IEC 60068-2-20
Temperature range	-30 °C to +80 °C