

TK 6422 LS

## FANTEK TK 6422 LS TOP LOAD TOWER 225KG WITH LOAD SENSE

---

The telescopic lifter model TK 6422 LS is a lifter designed to lift vertical loads up to 225 Kg and 6.4 meters in height. It features the LoadSense system, which allows monitoring the lifter load in accordance with EN-17206 requirements. Composed of 5 extendable steel profiles raised by a high-strength steel cable. Fixation of the tower section at the working height with an automatic steel safety pin. Legs with non-slip rubber supports. The entire system is operated by a manual winch with a double crank handle.

TK 6422 LS

3b6d7c41-9277-4177-b14b-703dc5d17908.png

dad63ed6-6a8f-4427-8aef-97832cf9556e.png

5934ffb6-e106-45f0-ba3c-8c99d6

c27e23e0-2d9f-4a37-80c2-daf012d83c1a.png

65baec88-c160-4288-b045-7dd27f35d480.png

da085660-64f2-4661-acc9-5d8ce

cc4e15bb-5ffa-4f62-8c2a-3be2dd2543d4.png

TK 6422 LS

# FANTEK TK 6422 LS TOP LOAD TOWER 225KG WITH LOAD SENSE

## PRODUCT DETAILS

### KEY FEATURES

Over 5 Meters Maximum Height

Load meter. Wire drive system

Leveling leg system

High load capacity

Upper insertion diameter: 35 mm

### SPECIFICATIONS

|                           |                                |
|---------------------------|--------------------------------|
| Material                  | Iron                           |
| Folded Height             | 1.95 m / 6.40 ft               |
| Extended base dimensions  | 2.65 x 2.65 m / 8.69 x 8.69 ft |
| Folded base dimensions    | 0.46 x 0.46 m / 1.51 x 1.51 ft |
| Maximum height            | 6.55 m / 21 ft                 |
| Minimum height            | 1.95 m / 6.40 ft               |
| Number of sections        | 5                              |
| Minimum Load              | 25 Kg / 55.12 lb               |
| Max load (mechanism mode) | 225 Kg / 496.04 lb             |
| Winch                     | 900 Kg / 1984.16 lb            |
| Cable diameter            | 6 mm / 0.24 in                 |
| Noise emission            | 75 dB                          |

TK 6422 LS

# FANTEK TK 6422 LS TOP LOAD TOWER 225KG WITH LOAD SENSE

|                              |                                                     |  |
|------------------------------|-----------------------------------------------------|--|
| Compatible accessories       | ATCMOS / ATCMOB / ATCLTS / ATC6FS / ATC29S / ATCBAS |  |
| Security systems             | LoadSense/Automatic locking system with safety pins |  |
| Standards and Certifications | EN-17206, CE, DGUV, BGV C1, BGG 912                 |  |
| Weight                       | 103 Kg / 227.08 lb                                  |  |
| Base diameter unfolded       | 2.65 m / 8.69 ft                                    |  |