

# SC42BK200PD SPEAKER CABLE XLR 3 PINS FEMALE - 1/4" JACK / 20 MT

These twinaxial speaker cable lines are a valid product to connect speaker systems with long cable run and large conductor areas or shorter bridge cables with lower power requirements. The section on 2.5 mm² satisfies a wide range of requirements. It is supplied with robust PE insulation and a flexible PVC jacket suitable to all sort of applications.







## SC42BK200PD SPEAKER CABLE XLR 3 PINS FEMALE - 1/4" JACK / 20 MT

## **PRODUCT DETAILS**

### **KEY FEATURES**

Connectors: XLR 3 pins female SP36XLF / 1/4" Jack, 2 poles, gold plated tip SP14PPE INCO

Twinaxial BC86SPK speaker cable

Wire area: 2x 2.50 mm<sup>2</sup>

Cable diameter: 8.7 mm

PVC jacket

PE insulation grants very low capacity

Flexibile, easy winding

Application: live, studio

Length: 20 mt

## **SPECIFICATIONS**

Wire area	2x 2.50 mm <sup>2</sup>
Cable diameter	8.7 mm

PVC jacket

Connectors XLR 3 pins female SP36XLF / 1/4" Jack, 2 poles, gold plated tip SP14PPE INCO

