


SC92BK015GD


## X-LEAD SC92GD SERIES SPEAKER CABLE, SPEAKON 4 POLES FEMALE - XLR 3 POLES MALE / 1.5 MT

These twinaxial speaker cable lines are a valid product to connect speaker systems with long cable run and large conductor areas or shorter bridge cables with lower power requirements. The section of 1.0 mm<sup>2</sup> satisfies a wide range of requirements. It is supplied with robust PE insulation and a flexible PVC jacket suitable to all sort of applications.



 SPK4M Neutrik Connector

 BC82 - BC84 SPK Speaker Cable

 SP61XNM NEUTRIK 3 Pin XLR Connector, Male Plug

SC92BK015GD

# X-LEAD SC92GD SERIES SPEAKER CABLE, SPEAKON 4 POLES FEMALE - XLR 3 POLES MALE / 1.5 MT

## PRODUCT DETAILS

### KEY FEATURES

Connectors: Speakon 4 poles female SPK4M / XLR 3 poles male SP61XNM INCO

Twinaxial BC82SPK speaker cable

Wire area: 1.00 mm<sup>2</sup>

Cable diameter: 7.0 mm

PVC jacket

PE insulation grants very low capacity

Flexible, easy winding

Application: live, studio

Length: 1.5 mt

### SPECIFICATIONS

Wire area	1.00 mm <sup>2</sup>
-----------	----------------------

Cable diameter	7.0 mm
----------------	--------

PVC jacket	
------------	--

Connectors	Speakon 4 poles female SPK4M / XLR 3 poles male SP61XNM INCO
------------	--