

CHECKLINE-15A

# 15" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

CHECKLINE Coaxial Stage Monitor Series is the answer to those rental companies, sound engineers, and bands who need robust, elegant, and handy tools on the stage, but without giving up on high-performance and sonic quality. All three models of the series offer full-range coaxial woofers. The Bi-Amp module delivers 350W (RMS)/ 1000W (Peak) power with absolute sound clarity and reliability. The internal DSP ensures maximum dynamics, overloads and overheating control, and offers 2 EQ factory presets (Full-range, Monitor) and other 5 user-defined, with different equalization curves designed for all main applications. Whether they are used as monitor, full-range speaker, front fill or delayed speaker for indoor/outdoor applications with large dimensions, the CHECKLINE series is the perfect ready-to-use solution for audio professionals.



CHECKLINE-15A

# 15" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

## PRODUCT DETAILS

### KEY FEATURES

- High-Performance and sonic clarity
- 1.000W (Peak) Class-D bi-amped power module
- 48kHz/24-bit DSP with 2+5 EQ presets, 3-band EQ, Low-Cut, Delay (up to 100m)
- Dual-Band Peak/Overload/Thermal Limiter
- Easy-to-Use DSP Graphic Interface with LCD display and Single Encoder
- Two combo inputs (XLR/6.3 jack with MIC/LINE switches)
- Stereo Line RCA Input
- Two boutique-quality microphone preamps
- Rugged, texture-painted plywood enclosure
- Sophisticated coaxial transducers
- 90°x90° sound coverage

### SPECIFICATIONS

System Type	Self-powered 15" two-way, coaxial
Frequency Range (-10 dB)	50 Hz - 20 KHz
Frequency Response (±3 dB)	59 Hz - 20 KHz
Coverage Pattern	90° x 90° nominal (HxV)
HF Horn	Coaxial (included)
Crossover Modes	Active / DSP

## CHECKLINE-15A

# 15" BI-AMPED COAXIAL STAGE MONITOR WITH BUILT-IN DSP

Crossover Frequency	2.200 Hz
Power Rating (Continuous/Program)	350W /1.000W
Maximum SPL	129 dB SPL peak
LF Driver	1x15"/1" coaxial transducer
Digital Sound Processor	48kHz/24bit
Input Connectors	2x XLR combo female (Mic/Line)
Input Impedance	9.09kohm (XLR Combo)
Output Connectors	1x XLR mix output, 1x XLR loop input C
Enclosure	15mm, birch plywood
Mounting	35 mm pole socket
Monitor Angle	32°
Transport	2 integrated handles
Finish	Black spot painting
Grille	Powder coated, black, perforated steel with acoustic transparent foam
Dimensions (WxHxD)	470 x 371.7x 520 mm
Net Weight	18 kg
Optional Accessories	CHECKLINE-15 BAG (SKU Code J130J)