



XY-118S

HIGH-POWER SUBWOOFER WITH AN 18-INCH, LOW-FREQUENCY DRIVER.

A versatile PA/monitor speaker series that is compact in size and perfect for near-field monitoring – yet can deliver high-quality sound to the corners of the room. Boasts multiple installment options for easy set up.



XY-118S

HIGH-POWER SUBWOOFER WITH AN 18-INCH, LOW-FREQUENCY DRIVER.

PRODUCT DETAILS

KEY FEATURES

- High-power subwoofer with an 18-inch, low-frequency driver.
- Capable of reproducing deep bass as low as 35 Hz without distortion.
- Strong pillars installed in the cabinet ensure rigidity against the most powerful bass.
- Requires an active crossover to set the necessary frequency range
- NL4 INPUT and LINK OUT connections as standard.
- Pole mount for quick set-up with other Pioneer products.
- Robust enclosure made from premium multi-laminate birch plywood.

SPECIFICATIONS

| | |
|-----------------------|--|
| Enclosure Type | Single driver, reflex-loaded subwoofer |
| Frequency Response | 35 Hz to 150 Hz |
| Sensitivity (1 W/1 m) | 97 dB (half space) |
| Nominal Impedance | 8 Ohm |
| Power Handling | 1000 W RMS, 2000 W Program |
| Maximum SPL | 127 dB cont., 133 dB peak (half space) |
| Driver Configuration | 18 inch (460 mm) neodymium LF cone driver |
| Connectors | 2 x Neutrik SpeakON™ NL4 |
| Dimensions (W×H×D) | 590 × 643 × 650 mm (23.2 × 25.3 × 25.6 inch) |

XY-118S

HIGH-POWER SUBWOOFER WITH AN 18-INCH, LOW-FREQUENCY DRIVER.

| | |
|----------------------------------|---|
| Weight | 52 kg (114.7 lbs) |
| Rigging and Hardware | 4 x flush handles (2 left/2 right), 1 x M20 polemount socket for mid/high enclosures, 4 x rubber feet (bottom) and 4 x mating recesses (top), 16 x threaded points M8 for 4 castors |
| Grille | Hex punched steel |
| Enclosure | 18 mm (0.7 inch) birch plywood |
| Finish | Impact-resistant, Black semi-matt textured |
| Suggested Power Amplifier | K10DSP |
| Accessories | polemount socket cover(-W model only) |