

NL4MMX

4-POLE SPEAKON ADAPTER

Lockable 4 pole speakON adapter.

NL4MMX

Links two NL2/4F*s together for cable extension. Changes gender to male when permanently locked on the cable.

Features permanent secure connection on a speakON cable connector using 2nd lock. Can be permanently attached to NL2/4F*.

01M1EE1BSEWHQ9WA27KRXPDJVX.jpg

NL4MMX

4-POLE SPEAKON ADAPTER

PRODUCT DETAILS

KEY FEATURES

4-pole speakON adapter with Quick Lock system for a secure and reliable connection

High durability and reliability, with more than 5,000 mating cycles

Silver-plated bronze contacts (4 μ m Ag) for excellent conductivity and low contact resistance

Robust glass-fiber-reinforced polyamide construction

SPECIFICATIONS

Gender	male
Contact resistance	? 3 m? (after lifetime)
Dielectric strength	4 kVdc (peak)
Insulation resistance	> 1 G? (after dampheat)
Rated current per contact	15 A rms continuous
Rated current per contact	30 A audiosignal, duty cycle 50 %
Rated voltage	250 V (Insulation)
Attention	speakON is NOT to be used as an AC mains or power supply connector!
Lifetime	> 5000 mating cycles
Locking device	Quick Lock
Contact plating	4 μ m Ag
Contacts	Bronze (CuSn6)
Insert	Polyamide (PA 6 30 % GR)
Shell	Polyamide (PA 6 30 % GR)
Flammability	UL 94 HB

NL4MMX

4-POLE SPEAKON ADAPTER

Solderability

Complies with IEC 68-2-20

Temperature range

-30 °C to +80 °C