

KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)

KZ1 I

The Lyzard-KZ1 I is an ultra-miniature point source speaker that belongs to the smallest mid-high family of K-array. Its new design features a compact, milled aluminum enclosure measuring 22 x 37 x 11 mm and weighing just 21g.

The speaker boasts a single 0.5" long-excursion neodymium magnet transducer that ensures uncompromising audio performance with minimal residual noise. It is the finest solution of audio technology, especially when it must be kept hidden out of sight in the environment or decor. With a horizontal and vertical coverage of 140° and a frequency response ranging from 500 Hz up to 18kHz, the KZ1 I delivers clear audio reproduction and excellent intelligibility. Its peak SPL of 86 dB is impressive for a speaker of such a small size.

It is the perfect product to integrate audio in retail, small lounges and bars, home residences, hotels, and museums, leaving both your eyes fulfilled and your ears satisfied with its unique and sleek design.

All Lyzard loudspeakers can be customized with any RAL color painting or come in different metal premium finishes to enhance their impressive aesthetics. To meet specific design requirements, dedicated versions suitable for recessed installation are offered.

*For a complete audio system, the Lyzards must be combined with one or more Truffle or Rumble subwoofers, powered by a Kommander amplifier.

94184289-18f3-41d5-906e-30fad4c4989d.webp

b31b0e01-d179-42eb-893e-f33f7a77a847.webp

83309252-64c4-47af-ab5d-ca2

IP64

KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)

HIGHLIGHTS



DESIGN AND SOUND IN HARMONY

Introducing the **Mark I Lyzard** micro-loudspeaker range, where premium audio meets stunning design. Featuring an ultra-sleek, minimalist body crafted from precision-milled aluminum, Lyzard is the perfect choice for discreet installations in intimate environments. With two different lengths and exceptional mid-high-range performance, Lyzard offers a superior sound experience with minimal visual impact.

MAXIMUM DISCRETION

With its size of a chocolate bar, Lyzard speaker blend easily into modern or classic architecture without compromising the aesthetics or the sound, as the design integrates naturally into any decor.



KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)



RECESS YOUR SOUND INTO PLASTERBOARD WALLS AND SUSPENDED CEILINGS

For applications where the loudspeakers have to completely disappear, the new **KZ1R I** and **KZ14R I** models allow you to completely recess the body of the speaker into surfaces like plasterboard walls and suspended ceilings.

EASIER INSTALLATION WITH THE MAGNET GRILL

The magnetic grille ensures quick and effortless surface installation.



KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)



CUSTOM COLORS AND PREMIUM FINISHES AVAILABLE UPON REQUEST

The Lizard series is offered in a semi-matte **black** or an elegant **white** finish and can be customized to match any **RAL** code.

Premium **brushed** or **polished** stainless steel finishes give the products a chameleon-like ability to reflect surrounding surfaces and blend in with the background.

Also available in **24K gold**-plated aluminum and Rose Gold for the most luxurious finish - ideal for prestigious design projects and upscale applications.

Lizards loudspeakers are manufactured to achieve exacting standards and are subject to rigorous quality control system in Italy.

KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)

PRODUCT DETAILS

KEY FEATURES

500 Hz-18kHz high bright frequency response
Euroblock connector incorporated
Both Horizontal and Vertical 140° coverage
86 dB SPL (peak)
Pocket size, discreet, resistant and durable

SPECIFICATIONS

Type	Passive Point Source
Transducers	0.5" Neodymium Magnet Woofer
Frequency Response	500 Hz - 18 kHz (-6 dB, with dedicated preset)
Max SPL	86 dB (peak, calculated using a signal with crest factor 4 [12dB] measured at 8 m then scaled at 1 m.)
Coverage	V. 140° H. 140°
Nominal Impedance	16 ?
Power Handling	3.5 W
Connectors	IN+ / IN- screw terminals
IP Rating	IP64
Dimensions (WxHxD)	22 x 37 x 11 mm (0.9 x 1.5 x 0.4 in.)
Weight	0.021 kg (0.04lbs.)

KZ1 I

0.5" ULTRA-MINIATURE PASSIVE POINT SOURCE 16 OHM SPEAKER (BLACK COLOR)

Material	Aluminum
Standard Colors	Black / White
Custom colors	Available in any RAL color
Premium Metal Finishes	Available in 24K Gold / Antique Gold / Rose Gold / Polished or Brushed Steel
Marine-grade Treatment	Not Available