

KTR24

## 1X4" ULTRA-COMPACT PASSIVE ALUMINUM ALLOY SUBWOOFER, 4 ? (BLACK COLOR)

The Truffle-KTR24 is the smallest model in the compact line of Truffle subwoofers, designed to deliver precise and controlled low-frequency reinforcement in home audio systems, hotel audio systems, retail store sound systems, and home entertainment surround sound systems, where discreet design and space efficiency are essential.

It combines lightweight construction, durability, and a minimalist aesthetic, featuring a 4" woofer paired with a 4" passive radiator delivering 45 Hz – 150 / 500 Hz (-6 dB) frequency response and up to 112 dB peak SPL.

A dedicated preset, loaded on board K-array amplifiers, ensures optimal performance and reliable operation in home subwoofer and installation-focused applications.

KTR24

498e857c-3add-49fc-8cb0-e6eb1231f75c.webp

d4665778-a1f5-4ee2-938a-1f9b7f2d62ea.webp

IP64

KTR24

# 1X4" ULTRA-COMPACT PASSIVE ALUMINUM ALLOY SUBWOOFER, 4 ? (BLACK COLOR)

## HIGHLIGHTS



### EXTREMELY COMPACT ALUMINUM ALLOY SUBWOOFERS

An impressively small low-end source designed to remain hidden from view and easily concealable.

## HIDDEN BUT POWERFUL

Because of longer wavelengths, low-end frequencies are able to pass through most obstacles which is precisely why the Truffle was designed to remain hidden from view.



KTR24

1X4" ULTRA-COMPACT PASSIVE ALUMINUM ALLOY SUBWOOFER, 4 ? (BLACK COLOR)

PRODUCT DETAILS

KEY FEATURES

|                                               |
|-----------------------------------------------|
| Crafted from aluminum alloy                   |
| Lightweight, durable and minimalist aesthetic |
| 4 ? nominal impedance                         |
| 45 Hz - 150 / 500 Hz frequency response       |
| IP64 Rated                                    |

SPECIFICATIONS

|                    |                                                     |
|--------------------|-----------------------------------------------------|
| Type               | Passive Subwoofer                                   |
| Transducers        | 1x 4" Woofer + 1x 4" passive radiator               |
| Frequency Response | 45 Hz - 150 / 500 Hz (-6 dB, with dedicated preset) |
| Max SPL            | 112 dB                                              |
| Coverage           | Omni                                                |
| Nominal Impedance  | 4 ?                                                 |
| Power Handling     | 60 W                                                |
| Connectors         | 2-pin Euroblock                                     |
| IP Rating          | IP64                                                |
| Dimensions (WxHxD) | 122 x 117 x 199 mm (4.8 x 4.6 x 7.8 in.)            |
| Weight             | 1.5 kg (3.31 lbs.)                                  |
| Material           | Aluminum                                            |

KTR24

**1X4" ULTRA-COMPACT PASSIVE ALUMINUM ALLOY  
SUBWOOFER, 4 ? (BLACK COLOR)**

---

|                        |               |
|------------------------|---------------|
| Standard Colors        | Black         |
| Custom colors          | Not Available |
| Premium Metal Finishes | Not Available |
| Marine-grade Treatment | Not Available |