

KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

KS4 I

The Thunder-KS4 I is a high-performance subwoofer line designed to deliver powerful and controlled low-frequency reinforcement for professional sound systems, live events, and installed audio applications. Despite its compact footprint, the KS4 I provides deep and dynamic bass while maintaining precision and clarity across the low-frequency range.

At its core, the system features 2 x 18" neodymium magnet woofer, delivering extended bass performance. Built with a polyurea-coated birch plywood enclosure and no bass reflex, the KS4 I combines durability with portability and controlled emission.

KS4 I integrates a Class D amplifier with DSP processing for advanced system control and supports power outputs, analog and digital connectivity and advanced networking. With built-in Web-App and K-framework3 software compatible, accessible via dedicated K-connect.

*White and Custom RAL finishes are available upon request and is also offered a passive version of the subwoofer (KS4P)

2aba3c6d-3b25-47c3-9e5d-bea8d59233c8.webp


f69eeb41-d711-4901-bb08-2857ebad5fe3.webp

IP53 Class-D Crossover

KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

HIGHLIGHTS




THUNDER: STRIKE THE PERFECT AUDIO BALANCE

Combined with the unique audio solutions of K-array, add exceptional lows to your frequency range for live sound events with a choice of five subwoofer models from the Thunder series present in both active and passive electronic versions.


INTEGRATED CARDIOID TECHNOLOGY

The THUNDER-KSCARDIO412P joins the Thunder family as a state-of-the-art cardioid subwoofer, engineered to deliver extremely powerful low-frequency output while drastically minimizing rear sound radiation. Designed for professional live sound and fixed installations, it ensures clean, focused bass that keeps back emissions to a minimum.



KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)



ULTIMATE SOUND CONTROL


Low frequencies have always been one of the most challenging aspects of system design. Their natural omnidirectional behavior makes control difficult, often resulting in unwanted energy on stage and a less defined sound.

The combination of integrated cardioid technology and advanced simulation environments allows low-frequency behavior to be predicted and shaped with precision.

This approach enables controlled directivity, reduced rear radiation, and a cleaner, more consistent acoustic experience across any application.


CRAFTED FOR HEAVY TOURING

The Thunder Series subs are built with a choice of Finnish birch plywood so it lightweight and incredibly resistant, making it the perfect speaker for audio rentals. The new polyurea paint and the cataphoresis treatment for the front grill, further treated with powder coating, also give greater resistance to the harsh weather environments often experienced on the road.



KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)





OBSESSION FOR DETAILS

The details can really make the difference, the side handles are elegantly integrated into the speaker body beautifully crafted for comfort. The M20 threaded flange on the top which is essential for combining with the speaker stands and pins of the Pinnacle and Axle systems, is made for steadiness with internal strong tubular brackets to give more stability.

ADAPTABLE EVEN OFF THE STAGE

Thanks to K-array's signature compact style, without trying to be defined as a design product the Thunder series can easily adapt to architectural installations or even wedding events in the open air where blending in is of great importance, also thanks to the possibility of a custom painting on demand.



EXTENDED LINE ARRAY



Among the Thunder-KS accessories, one of particular importance are the mechanics for hanging in arrays which allow it to be suspended in combination with the line array speakers of the Mugello family, and in clusters composed exclusively of subwoofers. This hardware also allows you to create arrays with corners, in order to follow the set-up of the main array.

KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

INFRA MODELS FOR CINEMA

Sound performance is essential for an unforgettable cinema experience. Equal to the powerful and engaging imagery as seen on the big screen, the Thunder-KS model reveals an untapped potential of cinema sound performance by extending the low-end response even further, making it an easier task to excite the public in vast squares and even arenas.



MORE THAN JUST SUBWOOFERS

In their active version, the Thunders are more than just subwoofers. They include powerful 4-ch class D amplifiers fully managed by sophisticated integrated DSP processors.



This combination allows the electronics of a Thunder to deliver not only the power signal to the subwoofer itself, but offers up to three additional channels of amplification and processing, thus becoming a complete control unit that allows you to drive an entire stereo system using only one active unit. Questo si trasforma anche in un grande vantaggio economico.

KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

POWERED BY INTELLIGENCE

Enhanced performance and easy tuning are now managed by the Integrated Electronic Brain (IEB) implemented into K-array amplifiers. More than a traditional DSP, the built-in micro electronics driven by the integrated operating system osKar features expansive sound processing, offering complete user control over the system performance.



DANTE ENABLED


K-array amplifiers come with Dante already enabled, with the license built directly into the unit for immediate use without any extra activation steps.

According to the IEB or IEB+ version, different digital channel counts are available, offering flexible network integration and expanded audio distribution options.

CUSTOM COLORS AVAILABLE UPON REQUEST

The Thunder series is offered in black or elegant white finish and can be customized to match any RAL code to better integrate them in a wide variety of venues.

Thunder subwoofers are manufactured to achieve exacting standards and are subject to rigorous quality control system in Italy.



KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

PRODUCT DETAILS

KEY FEATURES

- 2x18" neodymium magnet woofer
- Built in Class D audio amplifier module 4x 2500W @ 4Ω (can drive external loudspeakers)
- K-array Connect mobile app for easy wireless access to the DSP features
- K-framework designer and remote control software for advanced loudspeakers system management
- Onboard DSP featuring: Channel Grouping; 3 bands fully parametric Input EQ; 8 bands fully parametric Output EQ with Peaking, High-Shelf, Low-Shelf, High-Pass, Low-Pass, HP-Butterworth and LP-Butterworth filters; Dynamic limiters; Signal routing with freely assignable input-to-output signal path with level adjustment; Channel delay up to 230 ms
- osKar embedded: custom operating system running on quad core 1.5 GHz internal processor
- Bass reflex acoustic load with symmetric ports
- High density Finnish birch plywood cabinet for increased resistance and robustness
- Rugged Polyurea coating for improved environmental resistance
- Available in black or white or customizable paint over the entire RAL palette
- IP53 rating

SPECIFICATIONS

Type	Active subwoofer
Transducers	2x18" neodymium magnet woofer
Frequency Response	30 Hz - 150/450 Hz (-6 dB) crossover dependant
Max SPL	141 dB
Rated Power	2800 W (peak)

KS4 I

2X18" HIGH PERFORMANCE ACTIVE SUBWOOFER, 4 OHM (BLACK COLOR)

Coverage	Omni
Nominal Impedance	4 ?
Input Connectors	Line Input 2x XLR-F analog / AES3
Output Connectors	Line Output 2x XLR-M Link analog / AES3 - Speaker Output 2x SpeakON NL4
Networking and Data Connections	1x RJ45, 4x USB-A
Mains Connectors	PowerCON TRUE TOP
Remote Control	Wi-Fi dedicated Mobile APP, K-framework3 via wired Ethernet connection
Dimensions	1106 x 500 x 580 mm (43.5 x 19.7 x 22.8 in)
Weight	60 kg (132.3 lb)
Material	Polyurea coated birch plywood
Standard color	Black
Custom colors	Available in any RAL color
IP Rating	IP53 (in case of permanent, long lasting installation in critical environments (swimming pools, beaches, yachts..), we recommend to further protect the subwoofer. Contact K-array directly to discuss best protection practices)
Amp Module	4 ch Class D amp module
Amp Module Output Power	4x 2500W @ 4? (CTA-2006 Standard single channel driven)
Power Consumption	600 W @ 8 ? load, Pink noise, 1/4 rated power