

GC6T-RNW

# 6,5" CEILING SPEAKER 70/100V TRASFORMER IN-WALL ROUND WHITE

## 6,5" Ceiling Speaker

6,5" 2-way passive full range speaker for ceiling and in-wall installation. With a circular frameless grille design and orientable tweeter, GCF6 is the most versatile choice for residential and commercial environments such as apartments, villas, small home theaters, hotels, hospitals, bars and restaurants, corporate buildings.

GCF6 is available in 8 ohm for smaller sized, hi-fi applications as well as in 70/100V version (GCF6T) for large scale distributed sound installations where a very high number of speakers is required.

For optimal performance, depending on power/quantity needs, this speaker can be combined with any KGEAR amplifier (GA201, GA41/41L, GA43/43L, GA46/46L) and subwoofer (GS6, GCF8S, GWF8S). Available in black or white colour, the frameless magnetic grille can also be painted to match any environment.



GC6T-RNW

# 6,5" CEILING SPEAKER 70/100V TRASFORMER IN-WALL ROUND WHITE

## PRODUCT DETAILS

### SPECIFICATIONS

Type	Passive Fullrange Loudspeaker
Transducers	6,5" coaxial Woven Glass Fiber woofer with 0.75" Mylar dome tweeter
Frequency Response	60Hz-20kHz (-10 db)
Max.SPL?110dB (calculated using a signal with crest factor 4 (12dB) measured at 1 mt)	
Power handling	70v (2W 4W 8W 16W) / 100v (4W 8W 16W 32W)
Coverage	V. 130°   H. 130°
Dimensions ( Øouter [Øinner] x H )	Ø227 [210] x 87 mm ( 8.9 [8.3] x 3.4 in)
Maximum mounting depth	94 mm (3.7 in)
Weight	1,52 kg (3.3 lb)
Material	ABS
IP rating	IP54
Color	White