SYNCO XTALK XSTATION

WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

SYNCO XTALK XSTATION

The SYNCO XStation is a wireless intercom base station for the Xtalk Master, built to support larger teams and extended communication range. A single base station connects up to 20 headsets with a range of up to 400 m. Cascade two base stations to expand the system to 40 headsets with a communication range of up to 1,100 m.

By dividing the team into 5 groups, it ensures your crew hears only what matters - eliminating cross-talk and distractions for focused coordination on complex productions.

This station delivers universal integration, featuring a 4-wire interface for external intercom systems, a UAC interface for remote communication, and a PGM input for program audio monitoring. With the SYNCO Audio App, your entire setup - from group routing to audio settings - is managed from a single, centralized interface.

Built for fast-paced film production, TV broadcasting, and live events, the SYNCO XStation features a hybrid V-Mount and DC power supply, a flexible 1/4" tripod mount, and clear LED indicators to guarantee continuous uptime and effortless deployment.







Battery Powered Wireless Control

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

SYNCO XTALK XSTATION

WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

PRODUCT DETAILS

KEY FEATURES

- Scale up to 20 Users (40 users with 2 cascaded XStation)
- 400m range (1100m with 2 cascaded XStation) for rock-solid connectivity
- Efficient group management to hear only what is needed
- UAC for Remote Communication
- Monitor Program Audio (PGM) Input
- Universal 4-wire Interface
- Smart App Control for a centralized system management
- Dual Power Supply switching between battery and DC
- Standard 1/4" screw hole for mounting on tripods

SPECIFICATIONS

Range	400m (LOS)
RF Frequency Band	2.4GHz
Modulation	GFSK
Transmit Power	20dBm
RF Protocol	Proprietary
Latency	< 50ms
Frequency Response	150Hz~7KHz
Audio Sample Rate	8KHz, 16bit

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it

SYNCO XTALK XSTATION

WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

Power Supply	V-Mount battery; DC
Power Consumption	5W
Transmission Mode	Full-duplex
Operating Temperature	-15~45?

Via Enzo Ferrari 10
62017 Porto Recanati (MC), Italy
info@frenexport.it