

SYNCO XTALK XSTATION

WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

SYNCO XTALK XSTATION

The SYNCO XStation is a wireless intercom base station for the Xtalk Master, built to support larger teams and extended communication range. A single base station connects up to 20 headsets with a range of up to 400 m. Cascade two base stations to expand the system to 40 headsets with a communication range of up to 1,100 m.

By dividing the team into 5 groups, it ensures your crew hears only what matters - eliminating cross-talk and distractions for focused coordination on complex productions.

This station delivers universal integration, featuring a 4-wire interface for external intercom systems, a UAC interface for remote communication, and a PGM input for program audio monitoring. With the SYNCO Audio App, your entire setup - from group routing to audio settings - is managed from a single, centralized interface.

Built for fast-paced film production, TV broadcasting, and live events, the SYNCO XStation features a hybrid V-Mount and DC power supply, a flexible 1/4" tripod mount, and clear LED indicators to guarantee continuous uptime and effortless deployment.

01M145EQXDB8FHRPKCFHBRXJ5W.webp

01M145EPFX4MZE2NTGRW2Y2T0V.webp

01M145EQ9X3Y8K5B7GHNAZQKS0

Battery Powered Wireless Control

SYNCO XTALK XSTATION WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

PRODUCT DETAILS

KEY FEATURES

- Scale up to 20 Users (40 users with 2 cascaded XStation)
- 400m range (1100m with 2 cascaded XStation) for rock-solid connectivity
- Efficient group management to hear only what is needed
- UAC for Remote Communication
- Monitor Program Audio (PGM) Input
- Universal 4-wire Interface
- Smart App Control for a centralized system management
- Dual Power Supply switching between battery and DC
- Standard 1/4" screw hole for mounting on tripods

SPECIFICATIONS

Range	400m (LOS)
RF Frequency Band	2.4GHz
Modulation	GFSK
Transmit Power	20dBm
RF Protocol	Proprietary
Latency	< 50ms
Frequency Response	150Hz~7KHz
Audio Sample Rate	8KHz, 16bit

SYNCO XTALK XSTATION

WIRELESS INTERCOM BASE STATION FOR XTALK MASTER, 20 USERS, 400M RANGE, 5 GROUPS, UAC REMOTE COMMUNICATION, PGM INPUT, 4-WIRE COMPATIBILITY AND APP CONTROL

Power Supply	V-Mount battery; DC
Power Consumption	5W
Transmission Mode	Full-duplex
Operating Temperature	-15~45°