

XVISION HD (1TX+1RX) (TX + RX SETUP) WIRELESS HD VIDEO TRANSMISSION SYSTEM, 200M RANGE, MULTI-SCREEN MONITORING, 40MS LOW LATENCY

XVISION HD (1TX+1RX)

SYNCO XVision HD is a wireless HD video transmission system that elevates your production, live streaming, and creative projects to the next level of excellence.

Powered by Syncoder™ 5.0, it delivers stable long-range transmission with exceptional signal penetration, ensuring seamless 1080P/60fps image quality over 200m range.

The dual output ports on RX and the loop-out option on TX make it ideal for TVC, film production, live streaming, and large-scale events. Designed for efficient multi-user collaboration, it allows real-time monitoring across up to 9 monitoring ends, allowing directors, DPs, and crew members to stay in sync and ensuring precise control over every frame.

Its ultra-low 40ms latency enables real-time feedback, meeting professional-grade shooting demands. The 2W super low-power design extends battery life effortlessly, prevents overheating, and enhances user comfort for long hours of use. With an intuitive interface, a colour screen, and flexible power options, XVision HD provides a quiet, efficient, and hassle-free video transmission experience.

*This setup includes 1x Transmitter + 1x Receiver.

01M14EKC1EDEXJ40H8779HE3RA.webp

01M14EKAB000Y5C1YSCFF9MKHS.webp

01M14EKBHWVDWHAE94VFT61ZGJ.v

XVISION HD (1TX+1RX) (TX + RX SETUP) WIRELESS HD VIDEO TRANSMISSION SYSTEM, 200M RANGE, MULTI-SCREEN MONITORING, 40MS LOW LATENCY

PRODUCT DETAILS

KEY FEATURES

200m Wireless Video Transmission in 1080P/60fps

Multiple Outputs for 1-to-9 Video Monitoring

Ultra-Low 40ms Latency for Real-Time Viewing

Low-Power 2W Operation for Quiet Shooting

Flexible Power via NP-F Battery and USB-C Input

Real-Time Display with Smart, Easy Operation

Compact, Foldable Design for Easy Portability

SPECIFICATIONS

TRANSMITTER

Transmission Range200m

Power SupplyTYPE-C 5V2A / NPF Battery

Power Consumption<2W

Input Specification1080P@23.98/24/25/29.97/30/50/59.94/60P

Output Specification1080P@23.98/24/25/29.97/30/50/59.94/60P

Frequency Band5.180-5.825GHz

Transmit Power<20dBm

Latency40ms

Weight119g

XVISION HD (1TX+1RX) (TX + RX SETUP) WIRELESS HD VIDEO TRANSMISSION SYSTEM, 200M RANGE, MULTI-SCREEN MONITORING, 40MS LOW LATENCY

Dimensions	102 x 63 x 33mm
RECEIVER	
Transmission Range	200m
Latency	40ms
Interface	Output x2
Power Supply	TYPE-C 5V2A / NPF Battery
Power Consumption	<2W
Output Specification	1080P@23.98/24/25/29.97/30/50/59.94/60P
Frequency Band	5.180-5.825GHz
Transmit Power	<20dBm
Weight	119g
Dimensions	102 x 63 x 33mm