

Enhanced by the latest NUX technology innovation and upgraded algorithm, C-5RC fits perfectly with all types of Electric Guitars, Acoustic-electric Guitars, Bass Guitars and Ukuleles, no matter with active or passive, piezo or magnetic pickups.

C-5RC Wireless delivers the signal on 5.8 GHz frequency range. That's a global interference-free broadcasting range you can use everywhere without a signal break.

C-5RC features remarkable 24-bit audio quality, simple 'plug in and play' operation, super-low latency (<5 ms) and a solid signal for distances up to 30 meters / 100 feet in adequate conditions. C-5RC also comes with a portable Power Case to keep the wireless units charged – ideal design for when you are on the road.

















FRENEXPORT



HIGHLIGHTS



LONG LASTING BATTERY + POWER CASE

You can play for up to 4 hours non-stop and take advantage of your Power Case for 15 hours of extra power.

5.8GHZ BAND: LESS CROWDY!

Fewer interferences from other devices when you play at home.



FRENEXPORT





UNIVERSAL

Works great with any guitar, bass, ukulele with active, passive or piezo pick ups.

24-BIT/44.1KHZ WITH LESS THAN 5MS LATENCY

Crystal clear guitar tone and ultra low latency: you won't miss your cable.

SIMPLE PLUG'N PLAY AND SOLID SIGNAL UP TO 30 METERS

No need for setting anything: Auto matching system will do the job for you. And then you are in for up to 30 meters of freedom.

FRENEXPORT



PRODUCT DETAILS

KEY FEATURES

Crystal clear guitar tone audio @ 24-bit/44.1kHz with less than 5ms latency and Cable-tone function to preserve audio cable transmission quality

Works well with active, passive and piezo pickups with no buzzing/humming

5.8 GHz band ensures fewer interferences from other devices when you play on stage or at home

Auto matching system automatically pairs receiver/transmitter in the proper channel

Battery life: 4 hours of playing + 15 hours with Power Case

Can fit on all types of guitars, bass and ukuleles

Comes with an inbox charging/carrying case

SPECIFICATIONS

Range	up to 30 mt
Dynamic Range	108db
Operating Band	5.8GHz ISM Worldwide
THD+ Noise	<0.02% (1KHz@-10dbFS)
Frequency Response	20Hz – 20kHz
Built-in Battery Capacity	3.7V/500mA (Transmitter&Receiver)
Power Case Battery Capacity	4000mAh
Dimensions	107x25x26mm (LxWxH)
Weight	68gr

FRENEXPORT